

屋内照明器具特性	
品番 (品名)	L G W J 8 5 1 0 4 S
光源	LDA4 L - H - E17 / S / 4 ×1 440.0 lm
管理番号	K0128280 (0) DB 1
B Z 分類	BZ5 / 0.7 / BZ4

器具効率		26 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束		0 %	室指数	照明率 (X0.01)																Z	CM
下方光束		26 %																			
保守率		良 中 否	0.63	0.6	15	12	10	9	15	12	10	9	14	12	10	9	14	11	10	9	8
			0.6	0.8	18	15	13	11	17	15	13	11	17	14	13	11	16	14	12	11	11
			0.56	1.0	20	17	15	13	19	17	15	13	18	16	15	13	18	16	14	13	13
				1.25	21	19	17	15	21	18	17	15	20	18	16	15	19	18	16	15	15
下方投影面積		cm ²		1.5	22	20	18	17	22	20	18	17	21	19	18	17	20	19	18	17	16
等価発光面積			cm ²	2.0	24	22	20	19	23	22	20	19	22	21	20	19	22	21	19	19	18
取付 高さ	器具間隔最大限			2.5	25	23	22	21	24	23	21	20	23	22	21	20	23	22	21	20	19
	横方向 (A)		縦方向 (B)	3.0	25	24	23	22	25	24	22	22	24	23	22	21	23	22	22	21	20
H m	1.20 H m	1.23 H m		4.0	26	25	24	23	26	25	24	23	25	24	23	23	24	23	23	22	22
				5.0	26	26	25	24	26	25	25	24	25	25	24	23	25	24	24	23	22
				7.0	27	26	26	25	27	26	25	25	26	25	25	25	25	25	24	24	23
				10.0	27	27	26	26	27	27	26	26	26	26	26	25	26	25	25	25	24

