

屋内照明器具特性	
品番 (品名)	L G D 1 3 2 2 N
光源	L E D 5 0 0 0 _ 7 0 _ 5 0 0 × 1 5 0 0 . 0 l m
管理番号	K 0 1 9 0 2 4 4 (1) D B 1
B Z 分類	B Z 2 / 4 . 5 / B Z 3 / 6 . 0 / B Z 2

器具効率		1 0 0 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		1 0 0 %																					
保守率		良 中 否	0 . 6 7	0 . 6	7 0	6 0	5 4	5 0	6 9	6 0	5 4	5 0	6 7	5 9	5 4	5 0	6 5	5 8	5 3	5 0	4 8		
			0 . 6 3	0 . 8	7 8	6 9	6 3	5 9	7 7	6 9	6 3	5 9	7 4	6 7	6 2	5 9	7 2	6 6	6 2	5 8	5 7		
			0 . 5 6	1 . 0	8 3	7 5	6 9	6 5	8 2	7 4	6 9	6 5	8 0	7 3	6 8	6 5	7 7	7 2	6 8	6 4	6 3		
				1 . 2 5	8 8	8 1	7 5	7 1	8 6	8 0	7 5	7 1	8 4	7 8	7 4	7 0	8 2	7 7	7 3	7 0	6 8		
下方投影面積		c m ²	1 . 5	9 1	8 5	8 0	7 6	9 0	8 4	7 9	7 5	8 7	8 2	7 8	7 5	8 5	8 1	7 7	7 4	7 2			
			2 . 0	9 5	9 0	8 6	8 2	9 4	8 9	8 5	8 2	9 1	8 7	8 4	8 1	8 9	8 6	8 3	8 0	7 8			
取付 高さ	器具間隔最大限		2 . 5	9 8	9 3	9 0	8 6	9 6	9 2	8 9	8 6	9 4	9 0	8 7	8 5	9 2	8 9	8 6	8 4	8 2			
	横方向 (A)		縦方向 (B)		3 . 0	9 9	9 6	9 2	8 9	9 8	9 5	9 2	8 9	9 6	9 3	9 0	8 8	9 3	9 1	8 9	8 7		
H m	0 . 4 4 H m		0 . 4 4 H m		4 . 0	1 0 2	9 9	9 6	9 4	1 0 0	9 8	9 5	9 3	9 8	9 6	9 4	9 2	9 6	9 4	9 2			
					5 . 0	1 0 3	1 0 1	9 8	9 6	1 0 2	9 9	9 7	9 6	9 9	9 7	9 6	9 4	9 7	9 5	9 4			
					7 . 0	1 0 5	1 0 3	1 0 1	1 0 0	1 0 3	1 0 2	1 0 0	9 9	1 0 1	1 0 0	9 8	9 7	9 9	9 8	9 6			
					1 0 . 0	1 0 6	1 0 4	1 0 3	1 0 2	1 0 5	1 0 3	1 0 2	1 0 1	1 0 2	1 0 1	1 0 0	9 9	1 0 0	9 9	9 8			

