

屋内照明器具特性	
品番 (品名)	X E D 1 1 0 0 L
光源	L L D 2 0 0 0 L C T 1 × 1 5 3 1 . 0 l m
管理番号	K 0 1 9 0 4 7 4 (0) D R 1
B Z 分類	B Z 3

器具効率		63 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.63	0.6	39	32	28	25	38	32	28	25	37	31	28	25	36	31	27	25	24
			0.6	0.8	46	39	35	32	45	39	35	32	43	38	35	32	42	38	34	32	31
			0.56	1.0	50	44	40	37	49	44	40	37	47	43	39	37	46	42	39	37	35
				1.25	53	48	45	42	53	48	44	42	51	47	44	41	49	46	43	41	40
下方投影面積		cm ²		1.5	56	51	48	45	55	51	47	45	53	50	47	44	52	49	46	44	43
				2.0	59	55	52	50	58	55	52	49	56	53	51	49	55	52	50	48	47
取付高さ	器具間隔最大限			2.5	61	58	55	53	60	57	55	52	58	56	54	52	57	55	53	51	50
	横方向 (A) 縦方向 (B)			3.0	62	59	57	55	61	59	56	55	59	57	56	54	58	56	55	53	52
Hm	1.21Hm 1.21Hm			4.0	64	61	60	58	63	61	59	57	61	59	58	57	60	58	57	56	54
				5.0	64	63	61	60	64	62	61	59	62	61	59	58	61	59	58	57	56
				7.0	66	64	63	62	65	64	62	61	63	62	61	60	62	61	60	59	58
				10.0	66	65	65	64	66	65	64	63	64	63	63	62	63	62	61	61	59

