

屋内照明器具特性	
品番 (品名)	X E D 3 2 0 2 L
光源	L L D 4 0 0 0 L C T 1 × 1 8 4 5 . 0 l m
管理番号	K 0 1 7 5 9 8 2 (0) D R 1
B Z 分類	B Z 3

器具効率		5 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		0 %	下方光束	5 0 %	室指数	照明率 (X 0 . 0 1) Z C M																	
保守率						良	0 . 6 3	0 . 6	0 . 5 6	0 . 6	3 1	2 6	2 2	2 0	3 1	2 6	2 2	2 0	3 0	2 5	2 2	2 0	2 9
下方投影面積 等価発光面積		c m ²	c m ²	1 . 2 5	0 . 8	3 7	3 2	2 8	2 6	3 6	3 1	2 8	2 6	3 5	3 1	2 8	2 6	3 4	3 0	2 7	2 5	2 4	
					1 . 0	4 0	3 5	3 2	3 0	3 9	3 5	3 2	3 0	3 8	3 4	3 2	3 0	3 7	3 4	3 1	2 9	2 8	
					1 . 5	4 3	3 9	3 6	3 4	4 2	3 8	3 6	3 3	4 1	3 8	3 5	3 3	4 0	3 7	3 5	3 3	3 2	
取付高さ		H m	1 . 2 1 H m	1 . 2 1 H m	2 . 0	2 . 0	4 7	4 4	4 2	4 0	4 6	4 4	4 2	4 0	4 5	4 3	4 1	3 9	4 4	4 2	4 0	3 9	3 8
						2 . 5	4 9	4 6	4 4	4 2	4 8	4 6	4 4	4 2	4 7	4 5	4 3	4 2	4 5	4 4	4 2	4 1	4 0
						3 . 0	5 0	4 7	4 6	4 4	4 9	4 7	4 5	4 4	4 8	4 6	4 5	4 3	4 6	4 5	4 4	4 3	4 2
					4 . 0	5 1	4 9	4 8	4 6	5 0	4 9	4 7	4 6	4 9	4 8	4 6	4 5	4 8	4 7	4 6	4 5	4 4	
					5 . 0	5 1	5 0	4 9	4 8	5 1	5 0	4 9	4 8	5 0	4 9	4 8	4 7	4 8	4 8	4 7	4 6	4 5	
					7 . 0	5 2	5 1	5 0	5 0	5 2	5 1	5 0	4 9	5 0	5 0	4 9	4 8	4 9	4 9	4 8	4 8	4 6	4 5
					1 0 . 0	5 3	5 2	5 2	5 1	5 2	5 2	5 1	5 0	5 1	5 1	5 0	5 0	5 0	5 0	4 9	4 9	4 7	

