

屋内照明器具特性	
品番 (品名)	LGB15309
光源	LLD3020CU1 ×1 615.0 lm
管理番号	K0190061 (0) DR 1
BZ分類	BZ1

器具効率		81 %	反 射 率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		0 %	室指数	照明率 (X0.01)																		Z	C	M
下方光束		81 %																						
保守率		良	0.6	68	63	60	58	68	63	60	58	67	63	60	58	66	62	60	58	57				
		中	0.8	73	69	66	64	72	68	66	64	71	68	65	63	70	67	65	63	62				
		否	0.63	1.0	76	72	69	67	75	72	69	67	74	71	69	67	73	70	68	67	66			
			0.56	1.25	79	75	73	71	78	75	72	70	76	74	72	70	75	73	71	70	69			
下方投影面積		c m ²	1.5	80	77	75	73	79	77	75	73	78	76	74	72	77	75	73	72	71				
等価発光面積		c m ²	2.0	82	80	78	76	81	79	77	76	80	78	77	75	78	77	76	75	73				
取付 高さ	器具間隔最大限		2.5	83	81	80	78	83	81	79	78	81	80	78	77	80	78	77	76	75				
	横方向 (A)		縦方向 (B)	3.0	84	83	81	80	83	82	80	79	82	80	79	78	80	79	78	77	76			
H m	0.35 H m	0.35 H m	4.0	85	84	83	82	84	83	82	81	83	82	81	80	81	80	80	79	77				
			5.0	86	85	84	83	85	84	83	82	83	83	82	81	82	81	80	80	78				
			7.0	87	86	85	84	86	85	84	84	84	83	83	82	82	82	81	81	79				
			10.0	87	87	86	86	86	86	85	85	84	84	84	83	83	82	82	82	80				

