

屋内照明器具特性	
品番 (品名)	L G B 1 5 3 0 9
光源	LLD5000LCC1 ×1 1140.0 l m
管理番号	K0190075 (1) DR 1
B Z 分類	BZ3 / 0.7 / BZ2

器具効率		84 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.67	0.6	55	46	41	37	54	46	41	37	52	45	40	37	51	44	40	37	35
			0.63	0.8	64	56	51	47	63	56	51	47	61	55	50	47	59	54	50	47	45
			0.56	1.0	69	63	58	54	68	62	57	54	66	61	57	54	65	60	56	53	52
				1.25	74	68	64	60	73	67	63	60	71	66	63	60	69	65	62	59	58
下方投影面積 等価発光面積		c m ²		1.5	77	72	68	64	76	71	67	64	74	70	66	64	72	68	65	63	61
				2.0	81	76	73	70	79	76	72	70	77	74	71	69	75	73	70	68	67
				2.5	83	79	76	74	82	78	76	73	80	77	75	72	78	75	73	72	70
取付 高さ	器具間隔最大限			3.0	84	81	79	76	83	80	78	76	81	79	77	75	79	77	75	74	72
	横方向 (A)	縦方向 (B)		4.0	86	84	82	80	85	83	81	79	83	81	80	78	81	80	78	77	75
H m	1.27 H m	1.27 H m		5.0	87	85	83	82	86	84	83	81	84	83	81	80	82	81	80	79	77
				7.0	88	87	86	84	87	86	85	84	85	84	83	82	83	83	82	81	79
				10.0	89	88	87	86	88	87	86	86	86	85	85	84	84	84	83	83	80

