

屋内照明器具特性	
品番 (品名)	L G B 1 6 7 0 9
光源	L L D 3 0 2 0 L C E 1 × 1 7 9 5 . 0 l m
管理番号	K 0 1 9 0 0 2 7 (1) D R 1
B Z 分類	B Z 1

器具効率			8 6 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
					壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
					床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束			8 6 %	室指数	照明率 (X 0 . 0 1) Z C M																		
下方光束																							
保守率			良 中 否	0 . 6 7	0 . 6	7 1	6 6	6 2	6 0	7 0	6 5	6 2	6 0	6 9	6 5	6 2	6 0	6 8	6 4	6 1	5 9	5 9	
				0 . 6 3	0 . 8	7 6	7 2	6 8	6 6	7 6	7 1	6 8	6 6	7 4	7 1	6 8	6 6	7 3	7 0	6 7	6 6	6 5	
				0 . 5 6	1 . 0	8 0	7 6	7 3	7 0	7 9	7 5	7 2	7 0	7 8	7 4	7 2	7 0	7 6	7 3	7 1	6 9	6 8	
					1 . 2 5	8 2	7 9	7 6	7 4	8 2	7 8	7 6	7 4	8 0	7 7	7 5	7 3	7 9	7 6	7 4	7 3	7 2	
下方投影面積			c m ²	1 . 5	8 4	8 1	7 8	7 6	8 3	8 0	7 8	7 6	8 2	7 9	7 7	7 6	8 0	7 8	7 6	7 5	7 4		
等価発光面積				c m ²	2 . 0	8 6	8 4	8 2	8 0	8 5	8 3	8 1	7 9	8 4	8 2	8 0	7 9	8 2	8 1	7 9	7 8	7 7	
取付 高さ	器具間隔最大限			2 . 5	8 8	8 5	8 4	8 2	8 7	8 5	8 3	8 2	8 5	8 3	8 2	8 1	8 3	8 2	8 1	8 0	7 8		
	横方向 (A)		縦方向 (B)	3 . 0	8 9	8 7	8 5	8 4	8 8	8 6	8 4	8 3	8 6	8 4	8 3	8 2	8 4	8 3	8 2	8 1	7 9		
H m	0 . 4 3 H m		0 . 4 3 H m	4 . 0	9 0	8 8	8 7	8 6	8 9	8 7	8 6	8 5	8 7	8 6	8 5	8 4	8 5	8 4	8 4	8 3	8 1		
				5 . 0	9 0	8 9	8 8	8 7	8 9	8 8	8 7	8 6	8 7	8 7	8 6	8 5	8 6	8 5	8 4	8 4	8 2		
				7 . 0	9 1	9 0	8 9	8 9	9 0	8 9	8 8	8 8	8 8	8 8	8 7	8 6	8 6	8 6	8 5	8 5	8 3		
				1 0 . 0	9 1	9 1	9 0	9 0	9 1	9 0	8 9	8 9	8 9	8 8	8 8	8 7	8 7	8 7	8 6	8 6	8 4		

