

屋内照明器具特性	
品番 (品名)	L G B 1 6 7 0 9
光源	L L D 2 0 0 0 L C E 1 × 1 5 3 1 . 0 l m
管理番号	K 0 1 9 0 0 2 8 (1) D R 1
B Z 分類	B Z 4 / 0 . 7 / B Z 3

器具効率		77 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X 0 . 0 1)																Z C M
保守率		良 中 否	0 . 6 7	0 . 6	4 7	3 9	3 3	2 9	4 6	3 8	3 3	2 9	4 5	3 7	3 3	2 9	4 3	3 7	3 2	2 9	2 8
			0 . 6 3	0 . 8	5 6	4 8	4 3	3 9	5 5	4 8	4 3	3 9	5 3	4 7	4 2	3 9	5 1	4 6	4 2	3 9	3 7
			1 . 0	1 . 0	6 1	5 4	5 0	4 6	6 0	5 4	4 9	4 6	5 8	5 3	4 9	4 5	5 6	5 2	4 8	4 5	4 3
			0 . 5 6	1 . 2 5	6 6	6 0	5 5	5 1	6 5	5 9	5 5	5 1	6 2	5 8	5 4	5 1	6 1	5 6	5 3	5 0	4 9
下方投影面積		c m ²	1 . 5	6 8	6 3	5 9	5 5	6 7	6 2	5 8	5 5	6 5	6 1	5 7	5 5	6 3	6 0	5 7	5 4	5 2	
			2 . 0	7 2	6 8	6 4	6 1	7 1	6 7	6 3	6 1	6 9	6 5	6 2	6 0	6 7	6 4	6 1	5 9	5 7	
等価発光面積	c m ²	2 . 5	7 4	7 1	6 7	6 5	7 3	7 0	6 7	6 4	7 1	6 8	6 6	6 3	6 9	6 7	6 4	6 3	6 1		
		3 . 0	7 6	7 3	7 0	6 7	7 5	7 2	6 9	6 7	7 3	7 0	6 8	6 6	7 1	6 9	6 7	6 5	6 3		
H m	1 . 3 2 H m	1 . 3 2 H m	4 . 0	7 8	7 5	7 3	7 1	7 7	7 4	7 2	7 0	7 5	7 3	7 1	6 9	7 3	7 1	6 9	6 8	6 6	
			5 . 0	7 9	7 7	7 5	7 3	7 8	7 6	7 4	7 2	7 6	7 4	7 3	7 1	7 4	7 2	7 1	7 0	6 8	
			7 . 0	8 0	7 9	7 7	7 6	7 9	7 8	7 6	7 5	7 7	7 6	7 5	7 4	7 5	7 4	7 3	7 2	7 0	
			1 0 . 0	8 1	8 0	7 9	7 8	8 0	7 9	7 8	7 7	7 8	7 7	7 6	7 6	7 6	7 6	7 5	7 4	7 2	

