

屋内照明器具特性	
品番 (品名)	L G B 1 6 7 0 9
光源	LLD5000LCC1 ×1 1140.0 lm
管理番号	K0190075 (1) DR 1
B Z 分類	BZ3 / 0.7 / BZ2

器具効率		8 4 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
					床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
						照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 7	0 . 6	5 5	4 6	4 1	3 7	5 4	4 6	4 1	3 7	5 2	4 5	4 0	3 7	5 1	4 4	4 0	3 7	3 5	
			0 . 6 3	0 . 8	6 4	5 6	5 1	4 7	6 3	5 6	5 1	4 7	6 1	5 5	5 0	4 7	5 9	5 4	5 0	4 7	4 5	
			0 . 5 6	1 . 0	6 9	6 3	5 8	5 4	6 8	6 2	5 7	5 4	6 6	6 1	5 7	5 4	6 5	6 0	5 6	5 3	5 2	
				1 . 2 5	7 4	6 8	6 4	6 0	7 3	6 7	6 3	6 0	7 1	6 6	6 3	6 0	6 9	6 5	6 2	5 9	5 8	
下方投影面積 等価発光面積		c m ² c m ²	1 . 5	7 7	7 2	6 8	6 4	7 6	7 1	6 7	6 4	7 4	7 0	6 6	6 4	7 2	6 8	6 5	6 3	6 1		
			2 . 0	8 1	7 6	7 3	7 0	7 9	7 6	7 2	7 0	7 7	7 4	7 1	6 9	7 5	7 3	7 0	6 8	6 7		
			2 . 5	8 3	7 9	7 6	7 4	8 2	7 8	7 6	7 3	8 0	7 7	7 5	7 2	7 8	7 5	7 3	7 2	7 0		
			3 . 0	8 4	8 1	7 9	7 6	8 3	8 0	7 8	7 6	8 1	7 9	7 7	7 5	7 9	7 7	7 5	7 4	7 2		
H m	1 . 2 7 H m	1 . 2 7 H m	4 . 0	8 6	8 4	8 2	8 0	8 5	8 3	8 1	7 9	8 3	8 1	8 0	7 8	8 1	8 0	7 8	7 7	7 5		
			5 . 0	8 7	8 5	8 3	8 2	8 6	8 4	8 3	8 1	8 4	8 3	8 1	8 0	8 2	8 1	8 0	7 9	7 7		
			7 . 0	8 8	8 7	8 6	8 4	8 7	8 6	8 5	8 4	8 5	8 4	8 3	8 2	8 3	8 3	8 2	8 1	7 9		
			1 0 . 0	8 9	8 8	8 7	8 6	8 8	8 7	8 6	8 6	8 6	8 5	8 5	8 4	8 4	8 4	8 3	8 3	8 0		

