

屋内照明器具特性	
品番 (品名)	XLGB1544
光源	LLD40001CQ1 ×1 845.0 lm
管理番号	K0190056 (0) DR 1
BZ分類	BZ4/0.7/BZ3

器具効率		70 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		1 %	室指数	照明率 (X0.01)																			Z	CM
下方光束		69 %																						
保守率		良 中 否	0.67	0.6	43	35	30	27	42	35	30	27	40	34	30	27	39	33	29	26	25			
			0.63	0.8	51	44	39	36	50	43	39	35	48	42	38	35	46	41	38	35	34			
			0.56	1.0	55	49	45	41	54	49	45	41	53	48	44	41	51	47	43	41	39			
				1.25	59	54	50	47	58	53	49	46	56	52	49	46	55	51	48	46	44			
下方投影面積		cm ²	1.5	62	57	53	50	61	56	53	50	59	55	52	49	57	54	51	49	47				
等価発光面積		cm ²	2.0	65	61	58	55	64	60	57	55	62	59	56	54	60	58	56	54	52				
取付 高さ	器具間隔最大限		2.5	67	64	61	58	66	63	60	58	64	62	59	57	62	60	58	57	55				
	横方向 (A) 縦方向 (B)		3.0	69	66	63	61	68	65	62	60	66	63	61	60	64	62	60	59	57				
H m	1.33 H m	1.33 H m	4.0	70	68	66	64	69	67	65	64	67	66	64	63	66	64	63	62	60				
			5.0	71	69	68	66	70	69	67	65	68	67	66	64	67	65	64	63	61				
			7.0	72	71	70	68	71	70	69	68	70	69	68	67	68	67	66	65	63				
			10.0	73	72	71	70	72	71	71	70	71	70	69	68	69	68	68	67	65				

