

| 屋内照明器具特性 |                         |
|----------|-------------------------|
| 品番 (品名)  | XLGB1742                |
| 光源       | LLD4000VCE1 ×1 845.0 lm |
| 管理番号     | K0190026 ( 0 ) DR 1     |
| BZ分類     | BZ4 / 0.7 / BZ3         |

| 器具効率         |                     | 67 %            | 反射率  | 天井            | 80 % |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 %  |  |  |  |
|--------------|---------------------|-----------------|------|---------------|------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|------|--|--|--|
|              |                     |                 |      | 壁             | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 %  |  |  |  |
|              |                     |                 |      | 床             | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 %  |  |  |  |
| 上方光束<br>下方光束 |                     | 0 %<br>67 %     | 室指数  | 照明率 ( X0.01 ) |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    | Z CM |  |  |  |
| 保守率          |                     | 良<br>中<br>否     | 0.67 | 0.6           | 41   | 34 | 29 | 26 | 41   | 33 | 29 | 26 | 39   | 33 | 29 | 26 | 38   | 32 | 28 | 25 | 24   |  |  |  |
|              |                     |                 | 0.63 | 0.8           | 49   | 42 | 38 | 34 | 48   | 42 | 37 | 34 | 46   | 41 | 37 | 34 | 45   | 40 | 36 | 34 | 32   |  |  |  |
|              |                     |                 | 1.0  | 54            | 48   | 43 | 40 | 53 | 47   | 43 | 40 | 51 | 46   | 42 | 40 | 49 | 45   | 42 | 39 | 38 |      |  |  |  |
|              |                     |                 | 0.56 | 1.25          | 57   | 52 | 48 | 45 | 56   | 51 | 48 | 45 | 54   | 50 | 47 | 44 | 53   | 49 | 46 | 44 | 43   |  |  |  |
| 下方投影面積       |                     | cm <sup>2</sup> | 1.5  | 60            | 55   | 51 | 48 | 59 | 54   | 51 | 48 | 57 | 53   | 50 | 48 | 55 | 52   | 49 | 47 | 46 |      |  |  |  |
| 等価発光面積       |                     | cm <sup>2</sup> | 2.0  | 63            | 59   | 56 | 53 | 62 | 58   | 55 | 53 | 60 | 57   | 54 | 52 | 58 | 56   | 54 | 52 | 50 |      |  |  |  |
| 取付<br>高さ     | 器具間隔最大限             |                 | 2.5  | 65            | 62   | 59 | 56 | 64 | 61   | 58 | 56 | 62 | 59   | 57 | 55 | 60 | 58   | 56 | 55 | 53 |      |  |  |  |
|              | 横方向 ( A ) 縦方向 ( B ) |                 | 3.0  | 66            | 63   | 61 | 59 | 65 | 63   | 60 | 58 | 63 | 61   | 59 | 57 | 62 | 60   | 58 | 57 | 55 |      |  |  |  |
| H m          | 1.32 H m            | 1.32 H m        | 4.0  | 68            | 66   | 64 | 62 | 67 | 65   | 63 | 61 | 65 | 63   | 62 | 60 | 63 | 62   | 61 | 59 | 58 |      |  |  |  |
|              |                     |                 | 5.0  | 69            | 67   | 65 | 64 | 68 | 66   | 65 | 63 | 66 | 65   | 63 | 62 | 64 | 63   | 62 | 61 | 59 |      |  |  |  |
|              |                     |                 | 7.0  | 70            | 69   | 67 | 66 | 69 | 68   | 67 | 65 | 67 | 66   | 65 | 64 | 66 | 65   | 64 | 63 | 61 |      |  |  |  |
|              |                     |                 | 10.0 | 71            | 70   | 69 | 68 | 70 | 69   | 68 | 67 | 68 | 67   | 67 | 66 | 67 | 66   | 65 | 65 | 63 |      |  |  |  |

