

屋内照明器具特性	
品番 (品名)	L G B 1 6 1 5 4
光源	LLD2000LCE1 ×1 531.0 lm
管理番号	K0190090 (1) DR 1
BZ分類	BZ3/0.7/BZ2/1.8/BZ3

器具効率		70 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束 下方光束		1 % 69 %	室指数	照明率 (X0.01) Z CM																		
保守率		良 中 否	0.67	0.6	45	38	34	30	45	38	33	30	43	37	33	30	42	36	33	30	29	
			0.63	0.8	52	46	41	38	51	45	41	38	50	45	41	38	48	44	40	38	37	
			1.0	57	51	47	44	56	50	46	43	54	49	46	43	52	48	45	43	41		
			0.56	1.25	60	55	51	48	59	54	51	48	57	53	50	48	56	52	50	47	46	
下方投影面積		cm ²	1.5	63	58	54	51	62	57	54	51	60	56	53	51	58	55	52	50	49		
等価発光面積			2.0	66	62	59	56	65	61	58	56	63	60	57	55	61	59	56	55	53		
取付	器具間隔最大限		2.5	68	64	62	59	67	64	61	59	65	62	60	58	63	61	59	57	56		
高さ	横方向 (A) 縦方向 (B)		3.0	69	66	64	62	68	65	63	61	66	64	62	60	64	62	61	59	58		
H m	1.31 H m 1.31 H m		4.0	70	68	66	65	69	67	66	64	68	66	64	63	66	65	63	62	60		
			5.0	71	70	68	66	70	69	67	66	69	67	66	65	67	66	65	64	62		
			7.0	72	71	70	69	72	70	69	68	70	69	68	67	68	67	66	66	64		
			10.0	73	72	71	71	72	72	71	70	71	70	69	69	69	68	68	67	65		

