

屋内照明器具特性	
品番 (品名)	L G B 1 0 8 5 5
光源	LLD4000LCT1 ×1 845.0 l m
管理番号	K0190109 (1) DR 1
B Z 分類	BZ3 / 0.7 / BZ2 / 1.8 / BZ3

器具効率		67 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束 下方光束		0 % 67 %	室指数	照明率 (X0.01) Z C M																		
保守率		良 中 否	0.67	0.6	44	37	32	29	43	37	32	29	42	36	32	29	40	35	32	29	28	
			0.63	0.8	51	44	40	37	50	44	40	37	48	43	39	37	47	42	39	37	35	
			1.0	55	49	45	42	54	49	45	42	52	48	44	42	51	47	44	41	40		
			0.56	1.25	58	53	50	47	57	53	49	46	56	52	49	46	54	51	48	46	44	
下方投影面積		c m ²	1.5	61	56	53	50	60	55	52	50	58	54	51	49	56	53	51	49	47		
等価発光面積			c m ²	2.0	64	60	57	54	63	59	56	54	61	58	56	53	59	57	55	53	51	
2.5	65			62	60	57	64	62	59	57	63	60	58	56	61	59	57	56	54			
取付 高さ	器具間隔最大限		3.0	67	64	62	60	66	63	61	59	64	62	60	58	62	60	59	58	56		
	横方向 (A) 縦方向 (B)		4.0	68	66	64	62	67	65	64	62	65	64	62	61	64	62	61	60	58		
H m	1.32 H m	1.32 H m	5.0	69	67	66	64	68	67	65	64	66	65	64	63	65	64	63	62	60		
			7.0	70	69	68	67	69	68	67	66	68	67	66	65	66	65	64	64	62		
			10.0	71	70	69	68	70	69	68	68	68	68	67	66	67	66	66	65	63		

