

# 屋内照明器具特性

品番 (品名)	XAS1030V	
光源	LED3500_70_440 ×1	440.0 lm
管理番号	K0166938(0)D 1	
BZ分類	BZ1	

器具効率	101%	天井	80%				70%				50%				30%				0%				
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%				
上方光束	0%	反射率	壁	10%				10%				10%				10%				0%			
下方光束	101%		床	10%				10%				10%				10%				0%			
		室指数	照明率 (X0.01)																ZCM				
保守率	良	0.67	0.6	82	76	72	69	82	76	72	69	80	75	71	69	79	74	71	69	67			
	中	0.63	0.8	89	83	79	76	88	82	78	75	86	81	78	75	85	80	77	75	74			
	否	0.56	1.0	92	87	83	80	91	86	83	80	90	85	82	80	88	84	81	79	78			
下方投影面積	cm <sup>2</sup>	等価発光面積	cm <sup>2</sup>	1.25	95	91	87	84	94	90	87	84	93	89	86	84	91	88	85	83	82		
				1.5	98	93	90	87	97	93	90	87	95	91	89	86	93	90	88	86	84		
取付高さ	器具間隔最大限		Hm	0.40Hm	0.40Hm	2.5	102	99	97	94	101	98	96	94	99	97	95	93	97	95	93	92	90
	横方向 (A)	縦方向 (B)				3.0	103	101	98	96	102	100	98	96	100	98	96	95	98	96	95	94	91
Hm	0.40Hm	0.40Hm	4.0	105	103	101	99	103	102	100	98	101	100	98	97	99	98	97	96	93			
			5.0	106	104	102	101	104	103	101	100	102	101	100	99	100	99	98	97	95			
Hm	0.40Hm	0.40Hm	7.0	106	105	104	103	105	104	103	102	103	102	101	100	101	100	100	99	96			
			10.0	107	106	105	105	106	105	104	104	104	103	102	102	102	101	101	100	97			

