

屋内照明器具特性	
品番 (品名)	L G B 1 0 8 5 9
光源	LLD40001CQ1 ×1 845.0 l m
管理番号	K0190098 (1) DR 1
B Z 分類	BZ3 / 0.7 / BZ2 / 3.5 / BZ3 / 6.0 / BZ2

器具効率		63 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.67	0.6	41	35	31	28	40	34	30	28	39	34	30	28	38	33	30	28	27
			0.63	0.8	47	42	38	35	47	41	37	35	45	40	37	35	44	40	37	34	33
			0.56	1.0	51	46	42	40	50	46	42	39	49	45	42	39	48	44	41	39	38
				1.25	54	50	46	44	54	49	46	44	52	48	46	43	51	48	45	43	42
下方投影面積		cm ²		1.5	57	52	49	47	56	52	49	47	54	51	48	46	53	50	48	46	45
			等価発光面積	cm ²	2.0	59	56	53	51	58	55	53	51	57	54	52	50	55	53	51	50
取付 高さ	器具間隔最大限			2.5	61	58	56	54	60	58	55	53	59	56	55	53	57	55	54	52	51
	横方向 (A) 縦方向 (B)			3.0	62	60	58	56	61	59	57	55	60	58	56	55	58	57	55	54	53
H m	1.31 H m	1.31 H m		4.0	64	62	60	59	63	61	59	58	61	60	58	57	60	59	57	56	55
				5.0	64	63	61	60	64	62	61	60	62	61	60	59	61	60	59	58	56
				7.0	65	64	63	62	65	64	63	62	63	62	61	61	62	61	60	60	58
				10.0	66	65	65	64	65	65	64	63	64	63	63	62	62	62	61	61	59

