

屋内照明器具特性	
品番 (品名)	L G B 1 6 1 5 9
光源	LLD40402CQ1 (KAKUSAN) ×1 860.0 l m
管理番号	K0190100 (1) DR 1
B Z 分類	BZ3 / 0.7 / BZ2 / 1.4 / BZ3

器具効率		61 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束 下方光束		0 % 61 %	室指数	照明率 (X0.01) Z C M																		
保守率		良 中 否	0.67	0.6	40	34	30	27	39	33	30	27	38	33	29	27	37	32	29	27	26	
			0.63	0.8	46	40	36	34	45	40	36	33	44	39	36	33	42	38	35	33	32	
			1.0	50	44	41	38	49	44	41	38	47	43	40	38	46	42	40	37	36		
			0.56	1.25	53	48	45	42	52	48	44	42	50	47	44	42	49	46	43	41	40	
下方投影面積		c m ²	1.5	55	51	47	45	54	50	47	45	52	49	46	44	51	48	46	44	43		
等価発光面積			c m ²	2.0	57	54	51	49	57	53	51	49	55	52	50	48	53	51	49	48	46	
2.5	59			56	54	52	58	56	53	51	57	54	52	51	55	53	52	50	49			
取付 高さ	器具間隔最大限		3.0	60	58	56	54	59	57	55	53	58	56	54	53	56	55	53	52	50		
	横方向 (A) 縦方向 (B)		4.0	62	60	58	56	61	59	57	56	59	58	56	55	58	56	55	54	53		
H m	1.30 H m	1.30 H m	5.0	62	61	59	58	62	60	59	58	60	59	58	57	59	58	57	56	54		
			7.0	63	62	61	60	63	62	61	60	61	60	59	59	60	59	58	57	56		
			10.0	64	63	63	62	63	63	62	61	62	61	61	60	60	60	59	59	57		

