

屋内照明器具特性	
品番 (品名)	LGB16159
光源	LLD2020LCT1 ×1 460.0 lm
管理番号	K0190112 (1) DR1
BZ分類	BZ1

器具効率		90 %	反 射 率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		0 %	室指数	照明率 (X0.01)																		Z	C	M
下方光束		90 %																						
保守率		良	0.67	0.6	77	72	69	66	76	72	69	66	75	71	68	66	74	71	68	66	65			
		中	0.63	0.8	82	78	75	73	82	78	75	72	80	77	74	72	79	76	74	72	71			
		否	0.56	1.0	86	82	79	77	85	81	78	76	83	80	78	76	82	79	77	76	75			
				1.25	88	85	82	80	87	84	82	80	86	83	81	79	84	82	80	79	78			
下方投影面積		c m ²		1.5	90	87	84	82	89	86	84	82	87	85	83	82	86	84	82	81	80			
等価発光面積		c m ²		2.0	92	89	87	86	91	89	87	85	89	87	86	85	88	86	85	84	82			
取付 高さ	器具間隔最大限			2.5	93	91	89	88	92	90	89	87	90	89	88	86	89	88	86	85	84			
	横方向 (A)		縦方向 (B)	3.0	94	92	91	89	93	91	90	89	91	90	89	88	90	88	88	87	85			
H m	0.41 H m		0.41 H m	4.0	95	94	92	91	94	93	92	91	92	91	90	89	90	90	89	88	86			
				5.0	95	94	93	93	95	94	93	92	93	92	91	90	91	90	90	89	87			
				7.0	96	95	95	94	95	94	94	93	93	93	92	92	91	91	91	90	88			
				10.0	97	96	96	95	96	95	95	94	94	93	93	93	92	92	91	91	89			

