

| 屋内照明器具特性 |                                      |
|----------|--------------------------------------|
| 品番 (品名)  | L S E B 3 1 4 7 K                    |
| 光源       | LDA4 L - H - E17 / S / 4 ×1 440.0 lm |
| 管理番号     | K0170955 ( 0 ) DR 1                  |
| B Z 分類   | BZ5 / 0.9 / BZ4                      |

| 器具効率   |          | 60 %             | 反射率              | 天井            | 80 % |     |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |    |    |   |
|--------|----------|------------------|------------------|---------------|------|-----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|----|----|---|
|        |          |                  |                  | 壁             | 70   | 50  | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |    |    |   |
|        |          |                  |                  | 床             | 10 % |     |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |    |    |   |
| 上方光束   |          | 0 %              | 室指数              | 照明率 ( X0.01 ) |      |     |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     | Z  | C  | M |
| 下方光束   |          | 60 %             |                  |               |      |     |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |    |    |   |
| 保守率    |          | 良<br>中<br>否      | 0.67             | 0.6           | 34   | 27  | 22 | 19 | 33   | 26 | 22 | 18 | 32   | 26 | 21 | 18 | 30   | 25 | 21 | 18 | 17  |    |    |   |
|        |          |                  | 0.63             | 0.8           | 40   | 33  | 29 | 25 | 39   | 33 | 29 | 25 | 38   | 32 | 28 | 25 | 36   | 31 | 28 | 25 | 24  |    |    |   |
|        |          |                  | 0.56             | 1.0           | 45   | 38  | 34 | 30 | 44   | 38 | 34 | 30 | 42   | 37 | 33 | 30 | 40   | 36 | 33 | 30 | 29  |    |    |   |
|        |          |                  |                  | 1.25          | 48   | 43  | 39 | 36 | 48   | 42 | 38 | 35 | 46   | 41 | 38 | 35 | 44   | 40 | 37 | 35 | 34  |    |    |   |
| 下方投影面積 |          | c m <sup>2</sup> |                  | 1.5           | 51   | 46  | 42 | 39 | 50   | 46 | 42 | 39 | 48   | 44 | 41 | 39 | 47   | 43 | 41 | 38 | 37  |    |    |   |
| 等価発光面積 |          |                  | c m <sup>2</sup> | 2.0           | 55   | 50  | 47 | 44 | 54   | 50 | 47 | 44 | 52   | 49 | 46 | 44 | 50   | 48 | 45 | 43 | 42  |    |    |   |
| 取付高さ   | 器具間隔最大限  |                  |                  | 2.5           | 57   | 53  | 50 | 48 | 56   | 53 | 50 | 48 | 54   | 51 | 49 | 47 | 52   | 50 | 48 | 47 | 45  |    |    |   |
|        |          | 横方向 ( A )        |                  | 縦方向 ( B )     |      | 3.0 | 58 | 55 | 53   | 50 | 57 | 54 | 52   | 50 | 55 | 53 | 51   | 49 | 54 | 52 | 50  | 49 | 47 |   |
| H m    | 1.34 H m | 1.34 H m         | 4.0              | 60            | 58   | 55  | 54 | 59 | 57   | 55 | 53 | 57 | 56   | 54 | 53 | 56 | 54   | 53 | 52 | 50 |     |    |    |   |
|        |          |                  | 5.0              | 61            | 59   | 57  | 56 | 60 | 58   | 57 | 55 | 58 | 57   | 56 | 54 | 57 | 56   | 55 | 54 | 52 |     |    |    |   |
|        |          |                  | 7.0              | 62            | 61   | 59  | 58 | 61 | 60   | 59 | 58 | 60 | 59   | 58 | 57 | 58 | 57   | 57 | 56 | 54 |     |    |    |   |
|        |          |                  | 10.0             | 63            | 62   | 61  | 60 | 62 | 61   | 60 | 60 | 61 | 60   | 59 | 58 | 59 | 59   | 58 | 57 | 56 |     |    |    |   |

