

屋内照明器具特性	
品番 (品名)	L S E B 3 2 4 0 K
光源	LDA4 L - H - E17 / S / 4 ×1 440.0 l m
管理番号	K0123182 (0) DB 1
B Z 分類	BZ5 / 1.1 / BZ6

器具効率		77 % 上方光束 28 % 下方光束 49 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z C M
保守率		良 中 否	0.67	0.6	41	32	26	22	38	30	25	21	34	27	23	20	30	24	21	18	15
			0.63	0.8	46	38	32	28	44	36	31	27	38	32	28	24	33	29	25	22	18
			0.56	1.0	51	42	36	32	47	40	35	31	42	36	31	28	36	32	28	25	20
				1.25	54	47	41	36	51	44	39	35	45	39	35	31	39	35	31	28	23
下方投影面積		c m ²		1.5	57	50	44	40	54	47	42	38	47	42	38	34	41	37	33	31	25
			等価発光面積	c m ²	2.0	61	55	50	45	57	52	47	43	50	46	42	39	44	40	37	35
取付 高さ	器具間隔最大限			2.5	64	58	53	49	60	55	50	47	52	49	45	42	46	43	40	37	30
	横方向 (A) 縦方向 (B)			3.0	65	60	56	52	62	57	53	50	54	51	47	45	47	44	42	40	32
H m	0.76 H m 0.76 H m			4.0	68	64	60	57	64	60	57	54	56	53	51	48	49	47	45	43	34
				5.0	69	66	63	60	66	62	59	57	58	55	53	51	51	49	47	45	36
				7.0	71	69	66	63	67	65	62	60	60	58	56	54	52	51	49	48	39
				10.0	73	71	69	67	69	67	65	63	61	60	58	57	54	53	52	50	41

