

屋内照明器具特性	
品番 (品名)	L G D 9 0 1 0
光源	L L D 2 4 2 0 L C B 1 × 1 5 0 0 . 0 1 m
管理番号	K 0 1 9 1 4 4 8 (0) D B 1
B Z 分類	B Z 1

器具効率		9 5 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																		Z C M
下方光束		9 5 %																				
保守率		良 中 否	0 . 6 7	0 . 6	7 8	7 2	6 8	6 6	7 8	7 2	6 8	6 5	7 6	7 1	6 8	6 5	7 5	7 1	6 7	6 5	6 4	
			0 . 6 3	0 . 8	8 5	7 9	7 5	7 3	8 4	7 9	7 5	7 3	8 2	7 8	7 5	7 2	8 1	7 7	7 4	7 2	7 1	
			0 . 5 6	1 . 0	8 8	8 3	8 0	7 7	8 7	8 3	8 0	7 7	8 6	8 2	7 9	7 7	8 4	8 1	7 8	7 6	7 5	
				1 . 2 5	9 1	8 7	8 4	8 2	9 1	8 7	8 4	8 1	8 9	8 5	8 3	8 1	8 7	8 4	8 2	8 0	7 9	
下方投影面積		c m ²		1 . 5	9 3	9 0	8 7	8 4	9 3	8 9	8 6	8 4	9 1	8 8	8 5	8 4	8 9	8 7	8 5	8 3	8 1	
等価発光面積			c m ²	2 . 0	9 6	9 3	9 1	8 8	9 5	9 2	9 0	8 8	9 3	9 1	8 9	8 7	9 1	9 0	8 8	8 6	8 5	
取付 高さ	器具間隔最大限		2 . 5	9 8	9 5	9 3	9 1	9 7	9 4	9 2	9 1	9 5	9 3	9 1	9 0	9 3	9 1	9 0	8 9	8 7		
	横方向 (A)		縦方向 (B)	3 . 0	9 9	9 6	9 5	9 3	9 8	9 6	9 4	9 2	9 6	9 4	9 3	9 1	9 4	9 2	9 1	9 0	8 8	
H m	0 . 4 1 H m	0 . 4 1 H m	4 . 0	1 0 0	9 8	9 7	9 5	9 9	9 7	9 6	9 5	9 7	9 6	9 4	9 3	9 5	9 4	9 3	9 2	9 0		
			5 . 0	1 0 1	9 9	9 8	9 7	1 0 0	9 8	9 7	9 6	9 8	9 7	9 6	9 5	9 6	9 5	9 4	9 3	9 1		
			7 . 0	1 0 2	1 0 1	1 0 0	9 9	1 0 0	1 0 0	9 9	9 8	9 8	9 8	9 7	9 6	9 6	9 6	9 5	9 5	9 2		
			1 0 . 0	1 0 2	1 0 1	1 0 1	1 0 0	1 0 1	1 0 0	1 0 0	9 9	9 9	9 8	9 8	9 8	9 7	9 7	9 6	9 6	9 3		

