

屋内照明器具特性	
品番 (品名)	XS Z P 7 3 0 7 L
光源	LLD3401LCB1+LLD2401LCB1 ×1 1200.0 lm
管理番号	K0192199 (0) DB 1
B Z 分類	BZ3 / 1.1 / BZ2 / 1.8 / BZ3

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %			
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %			
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %			
上方光束		4 2 %	室指数	照明率 (X 0 . 0 1)																			Z C M	
下方光束		5 8 %																						
保守率		良 中 否	0 . 6 9	0 . 6	5 6	4 5	3 8	3 4	5 2	4 3	3 7	3 3	4 6	3 9	3 4	3 0	4 0	3 5	3 1	2 8	2 4			
			0 . 6 7	0 . 8	6 5	5 5	4 9	4 4	6 1	5 2	4 6	4 2	5 4	4 7	4 2	3 9	4 7	4 2	3 9	3 6	3 0			
			0 . 6 3	1 . 0	7 1	6 2	5 6	5 1	6 7	5 9	5 3	4 9	5 9	5 3	4 8	4 5	5 2	4 7	4 4	4 1	3 5			
				1 . 2 5	7 6	6 8	6 2	5 8	7 2	6 5	5 9	5 5	6 3	5 8	5 4	5 1	5 5	5 2	4 9	4 6	3 8			
下方投影面積		c m ²	1 . 5	8 0	7 3	6 7	6 3	7 5	6 9	6 4	6 0	6 6	6 1	5 8	5 5	5 8	5 5	5 2	4 9	4 1				
等価発光面積		c m ²	2 . 0	8 4	7 9	7 4	7 0	7 9	7 4	7 0	6 7	7 0	6 6	6 3	6 0	6 1	5 9	5 6	5 4	4 5				
取付 高さ	器具間隔最大限		2 . 5	8 7	8 2	7 8	7 5	8 2	7 8	7 4	7 1	7 3	6 9	6 7	6 4	6 4	6 1	5 9	5 7	4 7				
	横方向 (A)	縦方向 (B)	3 . 0	8 9	8 5	8 1	7 8	8 4	8 0	7 7	7 4	7 4	7 1	6 9	6 7	6 5	6 3	6 1	6 0	4 9				
H m	1 . 3 3 H m	1 . 3 3 H m	4 . 0	9 2	8 8	8 5	8 3	8 6	8 4	8 1	7 9	7 6	7 4	7 2	7 0	6 7	6 5	6 4	6 3	5 1				
			5 . 0	9 3	9 0	8 8	8 6	8 8	8 5	8 3	8 1	7 8	7 6	7 4	7 3	6 8	6 7	6 6	6 5	5 2				
			7 . 0	9 5	9 3	9 1	8 9	9 0	8 8	8 6	8 5	7 9	7 8	7 7	7 5	6 9	6 8	6 8	6 7	5 4				
			1 0 . 0	9 6	9 5	9 3	9 2	9 1	8 9	8 8	8 7	8 0	7 9	7 8	7 8	7 0	7 0	6 9	6 8	5 5				

