

屋内照明器具特性	
品番 (品名)	XSZR3020L
光源	LLD3420LCB1 × 1 700.0 l m
管理番号	K0192056 (0) DB 1
B Z 分類	BZ1

器具効率		86 %	反 射 率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束		86 %	室指数	照明率 (X0.01)																Z C M	
下方光束																					
保守率		良 中 否	0.6	69	63	60	57	69	63	60	57	67	63	59	57	66	62	59	57	56	
			0.8	75	70	66	64	74	70	66	64	73	69	66	63	72	68	65	63	62	
			1.0	79	74	71	68	78	74	70	68	76	73	70	68	75	72	69	67	66	
			0.56	1.25	82	78	75	72	81	77	74	72	79	76	74	72	78	75	73	71	70
下方投影面積		c m ²	1.5	84	80	77	75	83	79	77	75	81	78	76	74	80	77	75	74	72	
等価発光面積			c m ²	2.0	86	83	81	79	85	83	80	78	84	81	79	78	82	80	78	77	75
取付 高さ	器具間隔最大限		2.5	88	85	83	81	87	84	83	81	85	83	81	80	83	82	80	79	77	
	横方向 (A)		縦方向 (B)	3.0	89	87	85	83	88	86	84	83	86	84	83	82	84	83	82	81	79
H m	0.54 H m	0.54 H m	4.0	90	88	87	85	89	87	86	85	87	86	85	84	85	84	83	83	81	
			5.0	91	89	88	87	90	88	87	86	88	87	86	85	86	85	84	84	82	
			7.0	91	90	90	89	90	90	89	88	89	88	87	86	87	86	86	85	83	
			10.0	92	91	91	90	91	90	90	89	89	89	88	88	87	87	87	86	84	

