

屋内照明器具特性	
品番 (品名)	XSZR1021L
光源	L LD2421LCB1 ×1 500.0 l m
管理番号	K0192059 (0) DB 1
BZ分類	BZ1

器具効率		8 3 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		8 3 %																					
保守率		良	0 . 6 3	0 . 6	6 8	6 2	5 9	5 6	6 7	6 2	5 8	5 6	6 6	6 1	5 8	5 6	6 5	6 1	5 8	5 6	5 5		
		中	0 . 6	0 . 8	7 3	6 8	6 5	6 3	7 3	6 8	6 5	6 3	7 1	6 7	6 4	6 2	7 0	6 7	6 4	6 2	6 1		
		否	1 . 0	1 . 0	7 7	7 2	6 9	6 7	7 6	7 2	6 9	6 7	7 5	7 1	6 8	6 6	7 3	7 0	6 8	6 6	6 5		
			0 . 5 6	1 . 2 5	8 0	7 6	7 3	7 1	7 9	7 5	7 3	7 0	7 7	7 4	7 2	7 0	7 6	7 3	7 1	7 0	6 8		
下方投影面積		c m ²	1 . 5	8 1	7 8	7 5	7 3	8 1	7 7	7 5	7 3	7 9	7 6	7 4	7 3	7 8	7 5	7 4	7 2	7 1			
			2 . 0	8 4	8 1	7 9	7 7	8 3	8 0	7 8	7 7	8 1	7 9	7 7	7 6	8 0	7 8	7 6	7 5	7 4			
等価発光面積	c m ²	2 . 5	8 5	8 3	8 1	7 9	8 4	8 2	8 0	7 9	8 3	8 1	7 9	7 8	8 1	7 9	7 8	7 7	7 6				
		3 . 0	8 6	8 4	8 2	8 1	8 5	8 3	8 2	8 0	8 3	8 2	8 1	7 9	8 2	8 1	7 9	7 8	7 7				
H m	0 . 5 4 H m	0 . 5 4 H m	4 . 0	8 7	8 6	8 4	8 3	8 6	8 5	8 4	8 3	8 4	8 3	8 2	8 1	8 3	8 2	8 1	8 0	7 8			
			5 . 0	8 8	8 7	8 5	8 4	8 7	8 6	8 5	8 4	8 5	8 4	8 3	8 3	8 3	8 3	8 2	8 1	7 9			
			7 . 0	8 9	8 8	8 7	8 6	8 8	8 7	8 6	8 5	8 6	8 5	8 5	8 4	8 4	8 4	8 3	8 3	8 1			
			1 0 . 0	8 9	8 9	8 8	8 7	8 8	8 8	8 7	8 7	8 6	8 6	8 5	8 5	8 5	8 4	8 4	8 4	8 1			

