

屋内照明器具特性

| | | | | | | | | | | |
|---------|-----------------------------------|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | NNLK42523J + NNL4500ENT | | | | | | | | | |
| 光源 | LED5000_85_5200 ×1 5200.0 lm | | | | | | | | | |
| 管理番号 | K0130919 (8) DB1 | | | | | | | | | |
| BZ分類 | BZ5 | | | | | | | | | |

| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--------|------------------|---------|------|-----|-----|----|------|-----|----|----|------|----|----|----|------|----|----|---------------|-----|----|--|--|--|--|--|--|--|--|--|--|--|--|--|-----|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 器具効率 | 100 % | 天井 | 80 % | | | | 70 % | | | | 50 % | | | | 30 % | | | | 0 % | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0 % | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 床 | 10 % | | | | 10 % | | | | 10 % | | | | 10 % | | | | 0 % | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 上方光束 | 4 % | 室指数 | | | | | | | | | | | | | | | | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM | | | | | | | | | | | | | | | |
| 下方光束 | 96 % | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 保守率 | 良 中 否 | 0.83 | 0.6 | 55 | 42 | 34 | 29 | 53 | 42 | 34 | 29 | 51 | 40 | 33 | 28 | 48 | 39 | 33 | 28 | 26 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 0.81 | 0.8 | 65 | 53 | 45 | 39 | 63 | 52 | 44 | 38 | 60 | 50 | 43 | 38 | 57 | 48 | 42 | 37 | 35 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 0.77 | 1.0 | 71 | 60 | 52 | 46 | 69 | 59 | 51 | 46 | 66 | 57 | 50 | 45 | 62 | 55 | 49 | 44 | 42 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | 1.25 | 77 | 67 | 59 | 53 | 75 | 66 | 58 | 53 | 71 | 63 | 57 | 52 | 68 | 61 | 56 | 51 | 48 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 下方投影面積 | c m ² | 1.5 | 81 | 72 | 65 | 59 | 79 | 70 | 64 | 58 | 75 | 68 | 62 | 57 | 72 | 66 | 60 | 56 | 53 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 2.0 | 87 | 79 | 72 | 67 | 85 | 77 | 71 | 66 | 81 | 75 | 69 | 65 | 77 | 72 | 68 | 64 | 60 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 取付高さ | 器具間隔最大限 | | 2.5 | 90 | 84 | 78 | 73 | 88 | 82 | 77 | 72 | 85 | 79 | 74 | 70 | 81 | 76 | 72 | 69 | 66 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 93 | 87 | 82 | 77 | 91 | 85 | 80 | 76 | 87 | 82 | 78 | 75 | 84 | 80 | 76 | 73 | 69 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.5m | 1.99 m | 2.17 m | 4.0 | 96 | 91 | 87 | 83 | 94 | 90 | 86 | 82 | 91 | 87 | 83 | 80 | 87 | 84 | 81 | 78 | 75 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2 | 2.62 | 2.74 | 5.0 | 98 | 94 | 90 | 87 | 96 | 93 | 89 | 86 | 93 | 89 | 86 | 84 | 89 | 87 | 84 | 82 | 78 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2.5 | 3.26 | 3.32 | 7.0 | 101 | 97 | 95 | 92 | 99 | 96 | 93 | 91 | 95 | 93 | 90 | 88 | 92 | 90 | 88 | 86 | 82 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 3 | 3.89 | 3.92 | 10.0 | 102 | 100 | 98 | 96 | 101 | 99 | 96 | 95 | 97 | 95 | 94 | 92 | 94 | 92 | 91 | 90 | 86 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

