

屋内照明器具特性

品番 (品名)	NTS31240S+NTS92101	
光源	LED5000_70_745 x1	745.0 lm
管理番号	K0161313(0)DB1	
BZ分類	BZ4	

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	1%	床	10%				10%				10%				10%				0%	
下方光束	99%	室指数	照明率 (X0.01)																ZCM	
保守率	良 中 否 0.67 0.63 0.56	0.6	59	47	40	34	58	47	39	34	55	45	39	34	53	44	38	34	32	
		0.8	70	59	51	46	68	58	51	46	65	57	50	46	63	55	50	45	43	
		1.0	76	67	60	54	75	66	59	54	72	64	58	54	69	63	57	53	51	
		1.25	82	74	67	62	81	73	66	62	78	71	65	61	75	69	64	60	58	
下方投影面積	c m ²	1.5	86	78	72	67	85	77	72	67	82	75	70	66	79	74	69	66	63	
		2.0	91	85	80	75	90	84	79	75	87	82	77	74	84	80	76	73	70	
取付高さ	器具間隔最大限		2.5	95	89	84	80	93	88	84	80	90	86	82	79	87	84	81	78	75
	横方向 (A)	縦方向 (B)	3.0	97	92	88	84	95	91	87	83	92	89	85	82	90	86	84	81	78
H m	0.91H m	1.22H m	4.0	100	96	92	89	98	94	91	88	95	92	90	87	93	90	88	86	83
			5.0	101	98	95	92	100	97	94	92	97	94	92	90	94	92	90	89	86
			7.0	103	101	98	96	102	99	97	96	99	97	95	94	96	95	93	92	89
			10.0	105	103	101	100	103	102	100	99	101	99	98	97	98	97	96	95	92

