

屋内照明器具特性	
品番 (品名)	NTS82221W+NTS92201
光源	LED4000_85_1855 x1 1855.0lm
管理番号	K0166619 (1) DJ 1
BZ分類	BZ1

器具効率		101 %	反 射 率	天井	80 %				70 %				50 %				30 %				0 %						
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %						
				床	10 %				10 %				10 %				10 %				0 %						
上方光束		0 %	室指数	照明率 (X0.01)																				Z	C		M
下方光束		101 %																									
保守率		良 中 否	0.6	85	79	76	73	85	79	75	73	83	78	75	73	82	78	75	73	71							
			0.8	91	86	82	80	90	86	82	80	89	85	82	79	88	84	81	79	78							
			1.0	95	90	87	84	94	90	87	84	92	89	86	84	91	88	85	83	82							
			0.68	1.25	98	94	91	88	97	93	90	88	95	92	89	87	94	91	89	87	86						
下方投影面積		c m ²	1.5	100	96	93	91	99	95	93	91	97	94	92	90	95	93	91	89	88							
			等価発光面積		c m ²	2.0	102	99	97	95	101	98	96	94	99	97	95	94	97	96	94	93	91				
取付 高さ	器具間隔最大限		2.5	104	101	99	97	103	100	98	97	101	99	97	96	99	97	96	95	93							
	横方向 (A)		縦方向 (B)		3.0	105	102	101	99	104	102	100	98	101	100	98	97	100	98	97	96	94					
H m	0.36 H m		0.36 H m		4.0	106	104	103	101	105	103	102	101	103	101	100	99	101	100	99	98	96					
					5.0	106	105	104	103	105	104	103	102	103	102	101	100	101	100	100	99	97					
					7.0	107	106	105	104	106	105	104	104	104	103	103	102	101	101	101	100	98					
					10.0	108	107	106	106	107	106	105	105	105	104	103	103	102	102	102	101	99					

