

| 屋内照明器具特性 |                             |
|----------|-----------------------------|
| 品番 (品名)  | XNN2061PE                   |
| 光源       | LED3000_85_1220 ×1 1220.0lm |
| 管理番号     | K0190269(0)DB1              |
| BZ分類     | BZ4                         |

| 器具効率   |          | 100 %<br><br>上方光束<br>0 %<br>下方光束<br>100 % | 反射率  | 天井   | 80 % |      |                  |     | 70 % |      |     |    | 50 % |      |    |    | 30 % |      |    |    | 0 % |     |
|--------|----------|-------------------------------------------|------|------|------|------|------------------|-----|------|------|-----|----|------|------|----|----|------|------|----|----|-----|-----|
|        |          |                                           |      | 壁    | 70   | 50   | 30               | 10  | 70   | 50   | 30  | 10 | 70   | 50   | 30 | 10 | 70   | 50   | 30 | 10 | 0 % |     |
|        |          |                                           |      |      | 床    | 10 % |                  |     |      | 10 % |     |    |      | 10 % |    |    |      | 10 % |    |    |     | 0 % |
|        |          |                                           |      |      |      | 室指数  | 照明率 ( X0.01) ZCM |     |      |      |     |    |      |      |    |    |      |      |    |    |     |     |
| 保守率    |          | 良<br>中<br>否                               | 0.83 | 0.6  | 60   | 49   | 42               | 37  | 59   | 48   | 41  | 37 | 57   | 47   | 41 | 36 | 55   | 46   | 41 | 36 | 34  |     |
|        |          |                                           | 0.81 | 0.8  | 71   | 60   | 53               | 48  | 69   | 59   | 52  | 47 | 67   | 58   | 52 | 47 | 64   | 57   | 51 | 47 | 45  |     |
|        |          |                                           | 0.77 | 1.0  | 77   | 67   | 60               | 55  | 76   | 67   | 60  | 55 | 73   | 65   | 59 | 55 | 70   | 64   | 59 | 54 | 52  |     |
|        |          |                                           |      | 1.25 | 83   | 74   | 68               | 63  | 81   | 73   | 67  | 62 | 79   | 72   | 66 | 62 | 76   | 70   | 65 | 61 | 59  |     |
| 下方投影面積 |          | cm <sup>2</sup>                           |      | 1.5  | 87   | 79   | 73               | 68  | 85   | 78   | 72  | 68 | 82   | 76   | 71 | 67 | 80   | 74   | 70 | 66 | 64  |     |
|        |          |                                           |      | 2.0  | 92   | 85   | 80               | 76  | 90   | 84   | 79  | 75 | 87   | 82   | 78 | 74 | 85   | 81   | 77 | 74 | 71  |     |
| 等価発光面積 |          | cm <sup>2</sup>                           |      | 2.5  | 95   | 89   | 85               | 81  | 93   | 88   | 84  | 80 | 91   | 86   | 83 | 79 | 88   | 84   | 81 | 78 | 76  |     |
|        |          |                                           |      | 3.0  | 97   | 92   | 88               | 85  | 96   | 91   | 87  | 84 | 93   | 89   | 86 | 83 | 90   | 87   | 84 | 82 | 79  |     |
| H m    | 1.19 H m | 1.19 H m                                  |      | 4.0  | 100  | 96   | 93               | 90  | 98   | 95   | 92  | 89 | 96   | 93   | 90 | 88 | 93   | 91   | 89 | 87 | 84  |     |
|        |          |                                           |      | 5.0  | 102  | 98   | 96               | 93  | 100  | 97   | 95  | 92 | 98   | 95   | 93 | 91 | 95   | 93   | 91 | 89 | 87  |     |
|        |          |                                           |      | 7.0  | 103  | 101  | 99               | 97  | 102  | 100  | 98  | 96 | 100  | 98   | 96 | 95 | 97   | 96   | 94 | 93 | 90  |     |
|        |          |                                           |      | 10.0 | 105  | 103  | 102              | 100 | 104  | 102  | 101 | 99 | 101  | 100  | 99 | 97 | 99   | 98   | 97 | 96 | 93  |     |

