

屋内照明器具特性	
品番 (品名)	NNF 4 3 5 0 0
光源	LDL40S.N/14/26(2600A) ×3      2600.0 1 m
管理番号	K0126754(1)DR1
BZ分類	BZ5

器具効率	92 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	92 %	室指数	照明率 ( X0.01 )																ZCM	
保守率	良	0.81	0.6	5.2	4.0	3.3	2.8	5.0	4.0	3.3	2.8	4.8	3.9	3.2	2.7	4.6	3.8	3.2	2.7	2.5
	中	0.77	0.8	6.1	5.0	4.3	3.7	6.0	4.9	4.2	3.7	5.7	4.8	4.2	3.7	5.5	4.7	4.1	3.7	3.5
	否	0.68	1.0	6.7	5.7	5.0	4.4	6.6	5.6	4.9	4.4	6.3	5.5	4.9	4.4	6.0	5.3	4.8	4.3	4.1
			1.25	7.3	6.4	5.7	5.1	7.1	6.3	5.6	5.1	6.8	6.1	5.5	5.1	6.6	6.0	5.4	5.0	4.8
下方投影面積		cm <sup>2</sup>	1.5	7.7	6.9	6.2	5.7	7.5	6.8	6.1	5.7	7.2	6.6	6.0	5.6	7.0	6.4	5.9	5.5	5.3
等価発光面積		cm <sup>2</sup>	2.0	8.2	7.5	7.0	6.5	8.1	7.4	6.9	6.5	7.8	7.2	6.8	6.4	7.5	7.1	6.7	6.3	6.1
取付高さ	器具間隔最大限		2.5	8.6	8.0	7.5	7.0	8.4	7.9	7.4	7.0	8.1	7.7	7.3	6.9	7.9	7.5	7.1	6.8	6.6
	横方向 (A)	縦方向 (B)	3.0	8.8	8.3	7.8	7.5	8.7	8.2	7.8	7.4	8.4	8.0	7.6	7.3	8.1	7.8	7.5	7.2	7.0
1.5m	2.09 m	2.13 m	4.0	9.1	8.7	8.3	8.0	9.0	8.6	8.3	8.0	8.7	8.4	8.1	7.8	8.4	8.2	7.9	7.7	7.5
2	2.74	2.68	5.0	9.3	8.9	8.6	8.4	9.1	8.8	8.6	8.3	8.9	8.6	8.4	8.2	8.6	8.4	8.2	8.0	7.8
2.5	3.41	3.26	7.0	9.5	9.2	9.0	8.8	9.4	9.1	8.9	8.7	9.1	8.9	8.7	8.6	8.9	8.7	8.6	8.4	8.2
3	4.07	3.85	10.0	9.6	9.5	9.3	9.1	9.5	9.4	9.2	9.1	9.3	9.1	9.0	8.9	9.1	8.9	8.8	8.7	8.5

