

屋内照明器具特性	
品番 (品名)	NNF 8 1 2 6 8
光源	LDL110S. N/54/65K(6500) ×1 65000.0 1m
管理番号	K0129402(1)DB1
BZ分類	BZ6/0.7/BZ5/3.5/BZ6

器具効率	97%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	2%	床	10%				10%				10%				10%				0%	
下方光束	95%	室指数	照明率 (X0.01)																ZCM	
保守率	良 0.81 中 0.77 否 0.68	0.6	52	40	32	26	51	39	32	26	48	38	31	26	46	37	30	26	24	
		0.8	62	50	42	36	60	49	41	35	57	47	40	35	54	46	39	35	32	
		1.0	68	57	48	42	66	56	48	42	63	54	47	42	60	52	46	41	38	
		1.25	74	63	55	49	72	62	55	49	68	60	53	48	65	58	52	48	45	
下方投影面積	c m ²	1.5	78	68	61	55	76	67	60	54	72	64	58	53	69	62	57	52	50	
		2.0	83	75	68	63	81	74	67	62	78	71	66	61	74	69	64	60	57	
取付高さ	器具間隔最大限		2.5	87	80	73	68	85	78	73	68	81	76	71	66	78	73	69	65	62
	横方向 (A)	縦方向 (B)	3.0	89	83	77	73	88	82	76	72	84	79	74	70	80	76	73	69	66
1.5m	2.2m	2.81m	4.0	93	87	83	79	91	86	82	78	87	83	80	76	84	81	77	75	71
2	2.85	3.24	5.0	95	90	86	83	93	89	85	82	90	86	83	80	86	83	81	78	75
2.5	3.52	3.73	7.0	97	94	91	88	96	92	89	87	92	90	87	85	89	87	85	83	79
3	4.18	4.26	10.0	99	97	94	92	98	95	93	91	94	92	90	89	91	90	88	87	83

