

屋内照明器具特性	
品番 (品名)	NNF 8 2 2 6 8
光源	LDL110S. N/54/65K(6500) x2 65000.0 1m
管理番号	K0129401(3)DB1
BZ分類	BZ6/0.7/BZ5

器具効率	94%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	1%	床	10%				10%				10%				10%				0%	
下方光束	93%	室指数	照明率 ( X0.01 )																ZCM	
保守率	良 0.81 中 0.77 否 0.68	0.6	51	39	31	26	50	38	31	26	47	37	31	26	45	36	30	26	23	
		0.8	60	49	41	35	59	48	41	35	56	47	40	35	53	45	39	34	32	
		1.0	67	56	48	42	65	55	47	42	62	53	46	41	59	51	45	41	38	
		1.25	72	62	55	49	70	61	54	49	67	59	53	48	64	57	52	47	45	
下方投影面積	c m <sup>2</sup>	1.5	76	67	60	54	74	66	59	54	71	64	58	53	68	62	57	52	50	
		2.0	82	74	67	62	80	73	67	62	76	70	65	61	73	68	64	60	57	
取付高さ	器具間隔最大限		2.5	85	78	73	68	83	77	72	67	80	75	70	66	77	72	68	65	62
	横方向 (A)	縦方向 (B)	3.0	88	82	77	72	86	80	76	71	83	78	74	70	79	76	72	69	66
1.5m	2.2m	2.81m	4.0	91	86	82	78	89	85	81	77	86	82	79	76	83	80	77	74	71
2	2.86	3.24	5.0	93	89	85	82	91	87	84	81	88	85	82	79	85	82	80	78	75
2.5	3.52	3.73	7.0	95	92	89	87	94	91	88	86	91	88	86	84	88	86	84	82	79
3	4.19	4.26	10.0	97	95	93	91	96	93	91	90	93	91	89	88	90	88	87	86	82

