

屋内照明器具特性

品番 (品名)	NNFS 4 1 6 0 5									
光源	LDL40S.N/14/26(2600A) ×1 2600.0 l m									
管理番号	K0130756(0)DB1									
BZ分類	BZ5									

器具効率	94 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	94 %	室指数	照明率 (X0.01) ZCM																	
保守率	良 中 否	0.81	0.6	5.2	4.0	3.2	2.7	5.0	3.9	3.2	2.7	4.8	3.8	3.1	2.7	4.6	3.7	3.1	2.6	2.4
		0.77	0.8	6.1	4.9	4.2	3.6	5.9	4.9	4.1	3.6	5.7	4.7	4.1	3.6	5.4	4.6	4.0	3.5	3.3
			1.0	6.7	5.6	4.8	4.3	6.5	5.5	4.8	4.3	6.2	5.4	4.7	4.2	6.0	5.2	4.7	4.2	4.0
		0.68	1.25	7.3	6.3	5.5	5.0	7.1	6.2	5.5	4.9	6.8	6.0	5.4	4.9	6.5	5.8	5.3	4.9	4.6
下方投影面積	c m ²	1.5	7.7	6.8	6.1	5.5	7.5	6.7	6.0	5.5	7.2	6.5	5.9	5.4	6.9	6.3	5.8	5.4	5.1	
		2.0	8.2	7.4	6.8	6.3	8.0	7.3	6.7	6.3	7.7	7.1	6.6	6.2	7.4	6.9	6.5	6.1	5.9	
取付高さ	器具間隔最大限		2.5	8.6	7.9	7.3	6.9	8.4	7.8	7.3	6.8	8.1	7.6	7.1	6.7	7.8	7.4	7.0	6.6	6.4
	横方向 (A)	縦方向 (B)	3.0	8.8	8.2	7.7	7.3	8.6	8.1	7.7	7.2	8.4	7.9	7.5	7.1	8.1	7.7	7.4	7.0	6.8
1.5m	2.02 m	2.13 m	4.0	9.1	8.7	8.3	7.9	9.0	8.6	8.2	7.8	8.7	8.3	8.0	7.7	8.4	8.1	7.8	7.6	7.3
2	2.66	2.69	5.0	9.3	8.9	8.6	8.3	9.2	8.8	8.5	8.2	8.9	8.6	8.3	8.1	8.6	8.4	8.2	7.9	7.7
2.5	3.31	3.26	7.0	9.6	9.3	9.0	8.8	9.4	9.2	8.9	8.7	9.2	8.9	8.7	8.5	8.9	8.7	8.5	8.4	8.1
3	3.95	3.85	10.0	9.7	9.5	9.3	9.1	9.6	9.4	9.2	9.1	9.4	9.2	9.0	8.9	9.1	9.0	8.9	8.7	8.5

