

# 屋内照明器具特性

品番 (品名)	NNFS 4 1 7 3 5																
光源	LDL40S . N / 14 / 26 ( 2600A ) × 1                      2600.0 1 m																
管理番号	K0126222 ( * ) DB 1																
BZ分類	BZ5 / 4.5 / BZ4																

器具効率	94 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	0 %	室指数	照明率 ( X0.01 )																	ZCM	
下方光束	94 %																				
保守率	良 中 否	0.81	0.6	5.2	4.1	3.3	2.8	5.1	4.0	3.3	2.8	4.9	3.9	3.2	2.8	4.7	3.8	3.2	2.8	2.6	
		0.77	0.8	6.2	5.1	4.3	3.8	6.1	5.0	4.3	3.8	5.8	4.9	4.2	3.8	5.6	4.8	4.2	3.7	3.5	
			1.0	6.8	5.8	5.1	4.5	6.7	5.7	5.0	4.5	6.4	5.6	5.0	4.5	6.2	5.4	4.9	4.4	4.2	
		0.68	1.25	7.4	6.5	5.8	5.3	7.3	6.4	5.8	5.3	7.0	6.3	5.7	5.2	6.7	6.1	5.6	5.2	5.0	
下方投影面積	c m <sup>2</sup>	1.5	7.9	7.0	6.4	5.8	7.7	6.9	6.3	5.8	7.4	6.7	6.2	5.8	7.1	6.6	6.1	5.7	5.5		
		2.0	8.4	7.7	7.2	6.7	8.3	7.6	7.1	6.6	8.0	7.4	7.0	6.6	7.7	7.2	6.8	6.5	6.3		
取付高さ	器具間隔最大限		2.5	8.7	8.2	7.7	7.2	8.6	8.1	7.6	7.2	8.3	7.9	7.5	7.1	8.1	7.7	7.3	7.0	6.8	
	横方向 (A)	縦方向 (B)	3.0	9.0	8.5	8.0	7.7	8.8	8.4	8.0	7.6	8.6	8.2	7.8	7.5	8.3	8.0	7.7	7.4	7.2	
1.5m	2.17 m	2.16 m	4.0	9.3	8.9	8.5	8.2	9.1	8.8	8.4	8.2	8.9	8.6	8.3	8.0	8.6	8.4	8.1	7.9	7.7	
2	2.87	2.73	5.0	9.5	9.1	8.8	8.6	9.3	9.0	8.7	8.5	9.1	8.8	8.6	8.4	8.8	8.6	8.4	8.2	8.0	
2.5	3.57	3.3	7.0	9.7	9.4	9.2	9.0	9.5	9.3	9.1	8.9	9.3	9.1	8.9	8.8	9.1	8.9	8.8	8.6	8.3	
3	4.25	3.89	10.0	9.8	9.6	9.5	9.3	9.7	9.5	9.4	9.2	9.5	9.3	9.2	9.1	9.2	9.1	9.0	8.9	8.6	

