

屋内照明器具特性

品番 (品名)	NNFS 4 2 7 2 5									
光源	LDL40S.N/14/26(2600A) ×2 2600.0 1 m									
管理番号	K0126223(1)DB1									
BZ分類	BZ5									

器具効率	93 %	天井	80 %				70 %				50 %				30 %				0 %																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																																				
		床	10 %				10 %				10 %				10 %				0 %																																				
上方光束	0 %	室指数																		照明率 (X0.01)																		ZCM																	
下方光束	93 %																																																						
保守率	良 中 否	0.81	0.6	51	40	32	27	50	39	32	27	48	38	31	27	46	37	31	26	25																																			
		0.77	0.8	61	50	42	36	59	49	42	36	57	48	41	36	54	46	40	36	34																																			
		0.68	1.0	67	57	49	44	66	56	49	43	63	54	48	43	60	53	47	43	41																																			
			1.25	73	63	56	51	71	63	56	51	68	61	55	50	66	59	54	50	48																																			
下方投影面積	c m ²	1.5	77	68	62	56	75	67	61	56	72	66	60	55	70	64	59	55	53																																				
		2.0	82	75	69	65	81	74	69	64	78	72	68	63	75	70	66	63	60																																				
等価発光面積	c m ²	2.5	86	80	75	70	84	79	74	70	82	77	73	69	79	75	71	68	66																																				
		3.0	88	83	78	75	87	82	78	74	84	80	76	73	81	78	75	72	70																																				
取付高さ	器具間隔最大限		4.0	91	87	84	80	90	86	83	80	87	84	81	78	85	82	80	77	75																																			
	横方向 (A)	縦方向 (B)	5.0	93	90	87	84	92	89	86	83	89	87	84	82	87	85	83	81	78																																			
1.5m	2.16 m	2.16 m	7.0	95	93	91	88	94	92	90	88	92	90	88	86	89	88	86	85	82																																			
2	2.86	2.73	10.0	97	95	94	92	96	94	93	91	93	92	91	89	91	90	89	88	85																																			
2.5	3.55	3.31																																																					
3	4.23	3.89																																																					

