

屋内照明器具特性

品番 (品名)	NNF W4 1 0 0 1				
光源	LDL40S . N / 14 / 26 (2600A) × 1 2600.0 1 m				
管理番号	K0133769 (2) DB 1				
BZ分類	BZ6				

器具効率	98 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		21 %	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		77 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 (X0.01)																				ZCM
保守率	良	0.83	0.6	4.9	3.7	2.9	2.3	4.7	3.5	2.8	2.3	4.2	3.2	2.6	2.1	3.8	3.0	2.4	2.0	1.7	
	中	0.81	0.8	5.8	4.6	3.8	3.2	5.5	4.4	3.6	3.1	5.0	4.1	3.4	2.9	4.5	3.7	3.2	2.7	2.3	
	否	0.77	1.0	6.4	5.2	4.4	3.8	6.1	5.0	4.3	3.7	5.5	4.6	4.0	3.5	5.0	4.2	3.7	3.2	2.8	
	下方投影面積	c m ²		1.25	7.0	5.9	5.1	4.5	6.6	5.6	4.9	4.3	6.0	5.2	4.6	4.1	5.4	4.8	4.2	3.8	3.3
等価発光面積	c m ²		1.5	7.4	6.4	5.6	5.0	7.0	6.1	5.4	4.8	6.4	5.6	5.0	4.5	5.8	5.1	4.6	4.2	3.7	
	c m ²		2.0	7.9	7.1	6.4	5.8	7.6	6.8	6.1	5.6	6.9	6.2	5.7	5.2	6.2	5.7	5.3	4.9	4.2	
取付高さ	器具間隔最大限		2.5	8.3	7.5	6.9	6.3	7.9	7.2	6.6	6.1	7.2	6.6	6.2	5.7	6.6	6.1	5.7	5.3	4.7	
	横方向 (A)	縦方向 (B)																			
1.5m	2.21 m	2.14 m	3.0	8.5	7.9	7.3	6.8	8.2	7.6	7.0	6.6	7.5	7.0	6.5	6.1	6.8	6.4	6.0	5.7	5.0	
2	2.92	2.69	4.0	8.9	8.3	7.8	7.4	8.5	8.0	7.5	7.1	7.8	7.4	7.0	6.7	7.1	6.8	6.5	6.2	5.5	
2.5	3.62	3.27	5.0	9.1	8.6	8.2	7.8	8.7	8.3	7.9	7.5	8.0	7.7	7.3	7.0	7.3	7.1	6.8	6.5	5.8	
3	4.32	3.86	7.0	9.4	9.0	8.6	8.3	9.0	8.6	8.3	8.0	8.3	8.0	7.7	7.5	7.6	7.4	7.2	7.0	6.2	
			10.0	9.6	9.3	9.0	8.8	9.2	8.9	8.7	8.5	8.5	8.3	8.1	7.9	7.8	7.7	7.5	7.3	6.5	

