

屋内照明器具特性	
品番 (品名)	NNF W4 1 0 2 1
光源	LDL40S . N / 14 / 26 ( 2600A ) ×1      2600.0 1 m
管理番号	K0133636 ( 4 ) DB 1
BZ分類	BZ6

器具効率	93 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	21 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	72 %	室指数	照明率 ( X0.01 )																ZCM	
保守率	良 中 否 0.83 0.81 0.77	0.6	46	35	27	22	44	33	26	21	40	31	25	20	36	28	23	19	16	
		0.8	55	43	36	30	52	42	34	29	47	38	32	27	42	35	30	26	22	
		1.0	61	50	42	36	58	48	40	35	52	44	38	33	47	40	35	31	26	
		1.25	66	56	48	42	63	53	46	41	57	49	43	38	51	45	40	36	31	
下方投影面積	c m <sup>2</sup>	1.5	70	60	53	47	66	58	51	46	60	53	47	43	54	49	44	40	34	
		2.0	75	67	60	55	71	64	58	53	65	59	54	49	59	54	50	46	40	
取付高さ	器具間隔最大限		2.5	78	71	65	60	75	68	63	58	68	63	58	54	62	58	54	50	44
	横方向 (A)	縦方向 (B)	3.0	81	74	69	64	77	71	66	62	70	66	61	58	64	60	57	54	47
1.5m	2.24 m	2.13 m	4.0	84	79	74	70	80	76	71	67	74	70	66	63	67	64	61	58	51
2	2.95	2.68	5.0	86	81	77	74	82	78	75	71	76	72	69	66	69	66	64	62	54
2.5	3.66	3.24	7.0	88	85	82	79	85	82	79	76	78	75	73	71	72	70	68	66	58
3	4.37	3.83	10.0	90	88	85	83	87	84	82	80	80	78	76	74	74	72	71	69	61

