

屋内照明器具特性

品番 (品名)	NNF W4 2 0 0 1 K				
光源	LDL40S . N / 14 / 26 (2600A) × 2 2600.0 1 m				
管理番号	K0133768 (4) DB 1				
BZ分類	BZ6				

器具効率	97 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		18 %	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		79 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 (X0.01)																				ZCM
保守率	良	0.83	0.6	49	37	29	23	47	35	28	23	43	33	26	22	39	30	25	20	17	
	中	0.81	0.8	58	46	38	32	55	44	37	31	50	41	34	29	46	38	32	28	24	
	否	0.77	1.0	64	53	44	38	61	51	43	37	56	47	40	35	51	43	38	33	29	
			1.25	70	59	51	45	66	57	49	43	61	53	46	41	55	49	43	39	34	
下方投影面積	c m ²		1.5	74	64	56	50	70	61	54	48	64	57	51	46	59	53	48	43	38	
	等価発光面積		c m ²	2.0	79	71	64	58	76	68	62	56	70	63	58	53	64	58	54	50	44
取付高さ	器具間隔最大限		2.5	83	75	69	63	79	72	67	62	73	67	62	58	67	62	58	55	49	
	横方向 (A)	縦方向 (B)	3.0	85	79	73	68	82	76	71	66	76	70	66	62	69	65	62	58	52	
1.5m	2.22 m	2.16 m	4.0	89	83	78	74	85	80	76	72	79	75	71	68	73	69	66	64	57	
2	2.92	2.71	5.0	91	86	82	78	88	83	79	76	81	78	74	71	75	72	69	67	60	
2.5	3.63	3.29	7.0	94	90	86	83	90	87	84	81	84	81	78	76	78	75	73	71	64	
3	4.33	3.88	10.0	96	93	90	88	92	90	87	85	86	84	82	80	80	78	77	75	68	

