

屋内照明器具特性	
品番(品名)	NNF W4 2 0 2 1 K
光源	LDL40S.N/14/26(2600A) ×2      2600.0lm
管理番号	K0133634(4)DB1
BZ分類	BZ6

器具効率	89%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	17%	床	10%				10%				10%				10%				0%	
下方光束	72%	室指数	照明率 (X0.01)																ZCM	
保守率	良 0.83 中 0.81 否 0.77	0.6	45	33	26	21	43	32	25	21	39	30	24	19	35	28	22	18	16	
		0.8	53	42	34	29	50	40	33	28	46	37	31	27	41	34	29	25	22	
		1.0	58	48	40	34	55	46	39	34	50	42	36	32	46	39	34	30	26	
		1.25	63	53	46	40	60	51	45	39	55	48	42	37	50	44	39	35	31	
下方投影面積	c m <sup>2</sup>	1.5	67	58	51	45	64	56	49	44	58	51	46	41	53	48	43	39	34	
		2.0	72	64	58	52	69	62	56	51	63	57	52	48	58	53	49	45	40	
取付高さ	器具間隔最大限		2.5	75	68	62	57	72	66	60	56	66	61	57	53	61	56	53	49	44
	横方向(A)	縦方向(B)	3.0	78	71	66	61	74	69	64	60	69	64	60	56	63	59	56	53	47
1.5m	2.2m	2.14m	4.0	81	76	71	67	78	73	69	65	72	68	64	61	66	63	60	57	51
2	2.89	2.69	5.0	83	78	74	71	80	76	72	69	74	70	67	65	68	65	63	61	54
2.5	3.6	3.27	7.0	85	82	79	76	82	79	76	73	76	74	71	69	70	68	66	65	58
3	4.29	3.86	10.0	87	84	82	80	84	82	79	77	78	76	74	73	73	71	70	68	61

