

屋内照明器具特性

品番（品名）	S L W4 5 8 4 0
光源	L E D 2 7 0 0 _ 7 0 _ 1 1 0 x 1 1 1 0 . 0 l m
管理番号	K 0 1 5 1 8 1 4 (0) D B 1
B Z 分類	B Z 1 0 / 1 . 4 / B Z 9

器具効率		100 %	反 射 率	天井	80 %				70 %				50 %				30 %				0 %
上方光束		81 %		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束		19 %		床	10 %				10 %				10 %				10 %				0 %
			室指数	照明率 (X0.01)																	ZCM
保守率		良	0.69	0.6	43	31	24	19	37	28	21	17	27	20	16	12	18	13	10	8	1
		中	0.67	0.8	51	40	32	27	44	35	28	24	32	26	21	17	22	17	14	11	2
		否	0.63	1.0	57	46	39	33	49	41	34	29	36	30	25	22	24	20	17	14	3
				1.25	62	52	45	39	54	46	40	35	40	34	30	26	27	23	20	18	5
下方投影面積		c m ²		1.5	66	57	50	44	58	50	44	39	43	37	33	30	29	25	23	20	6
等価発光面積		c m ²		2.0	71	63	57	52	63	56	51	46	46	42	38	35	32	29	26	24	7
取付	器具間隔最大限			2.5	74	68	62	57	66	60	55	51	49	45	42	39	33	31	29	27	9
高さ	横方向 (A)		縦方向 (B)	3.0	77	71	66	61	68	63	59	55	51	47	44	42	35	33	31	29	10
H _m	0.00 H _m	0.00 H _m	4.0	80	75	71	67	71	67	63	60	53	50	48	45	37	35	33	31	11	
			5.0	82	78	74	71	72	69	66	63	55	52	50	48	38	36	35	33	12	
			7.0	84	81	78	75	75	72	70	67	57	55	53	51	39	38	37	36	13	
			10.0	86	84	81	79	76	74	72	71	58	57	55	54	41	40	39	38	14	

