

屋内照明器具特性	
品番 (品名)	S L B 8 1 8 7 9
光源	LED2700_70_1820 ×1 1820.0 lm
管理番号	K0192612 (0) DR 1
B Z 分類	B Z 7

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
上方光束		31 %	室指数	照明率 (X0.01)																	Z	C	M
下方光束		69 %																					
保守率		良 中 否	0.67	0.6	47	35	26	21	44	33	25	20	39	29	23	18	34	26	20	16	12		
			0.63	0.8	56	43	35	28	53	41	33	27	46	37	30	25	40	32	27	22	17		
			1.0	62	50	41	35	58	47	39	33	51	42	35	30	44	37	32	27	21			
			0.56	1.25	68	56	48	41	64	53	45	39	56	47	41	36	49	42	37	32	25		
下方投影面積		cm ²	1.5	72	61	53	46	67	58	50	44	59	52	45	40	52	46	40	36	29			
等価発光面積		cm ²	2.0	77	68	60	54	73	65	58	52	64	58	52	47	57	51	46	42	34			
取付 高さ	器具間隔最大限		2.5	81	73	66	60	77	69	63	57	68	62	57	52	60	55	51	47	38			
	横方向 (A)	縦方向 (B)	3.0	84	76	70	64	79	72	67	62	70	65	60	56	62	58	54	50	41			
1.5m	2.16 m	2.15 m	4.0	87	81	76	71	83	77	72	68	74	69	65	61	65	62	59	55	46			
2	2.85	2.72	5.0	90	84	80	75	85	80	76	72	76	72	69	65	68	65	62	59	49			
2.5	3.53	3.31	7.0	93	88	84	81	88	84	81	77	79	76	73	70	71	68	66	63	53			
3	4.23	3.91	10.0	95	92	89	86	90	87	85	82	81	79	77	74	73	71	69	67	56			

