

屋内照明器具特性	
品番 (品名)	S L R 1 0 3 2 N
光源	L E D 5 0 0 0 _ 7 0 _ 2 2 3 × 1 2 2 3 . 0 l m
管理番号	K 0 1 6 1 9 0 7 (1) D B 1
B Z 分類	B Z 1

器具効率		1 0 0 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
上方光束		0 %	室指数	床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
下方光束		1 0 0 %		照明率 (X 0 . 0 1) Z C M																	
保守率		良 中 否	0 . 6	9 6	9 3	9 1	8 9	9 6	9 3	9 1	8 9	9 5	9 2	9 0	8 9	9 4	9 2	9 0	8 9	8 8	
			0 . 8	9 9	9 6	9 4	9 2	9 8	9 6	9 4	9 2	9 7	9 5	9 3	9 2	9 6	9 4	9 3	9 2	9 1	
			1 . 0	1 0 1	9 8	9 6	9 5	1 0 0	9 8	9 6	9 4	9 9	9 7	9 5	9 4	9 8	9 6	9 5	9 4	9 3	
			0 . 5 6																		
下方投影面積 等価発光面積		c m ² c m ²	1 . 2 5	1 0 2	1 0 0	9 8	9 7	1 0 1	9 9	9 8	9 6	1 0 0	9 8	9 7	9 6	9 9	9 7	9 6	9 5	9 4	
			1 . 5	1 0 3	1 0 1	9 9	9 8	1 0 2	1 0 0	9 9	9 8	1 0 1	9 9	9 8	9 7	1 0 0	9 8	9 7	9 6	9 5	
取付 高さ		器具間隔最大限 横方向 (A) 縦方向 (B)	2 . 0	1 0 4	1 0 3	1 0 1	1 0 0	1 0 4	1 0 2	1 0 1	9 9	1 0 2	1 0 1	9 9	9 9	1 0 0	9 9	9 8	9 8	9 6	
			2 . 5	1 0 5	1 0 4	1 0 2	1 0 1	1 0 4	1 0 3	1 0 2	1 0 1	1 0 2	1 0 1	1 0 0	1 0 0	1 0 1	1 0 0	9 9	9 9	9 7	
H m	0 . 3 7 H m	0 . 3 7 H m	3 . 0	1 0 6	1 0 4	1 0 3	1 0 2	1 0 5	1 0 3	1 0 2	1 0 1	1 0 3	1 0 2	1 0 1	1 0 0	1 0 1	1 0 0	1 0 0	9 9	9 7	
			4 . 0	1 0 6	1 0 5	1 0 4	1 0 3	1 0 5	1 0 4	1 0 3	1 0 3	1 0 3	1 0 3	1 0 2	1 0 1	1 0 2	1 0 1	1 0 0	1 0 0	9 8	
			5 . 0	1 0 7	1 0 6	1 0 5	1 0 4	1 0 6	1 0 5	1 0 4	1 0 3	1 0 4	1 0 3	1 0 3	1 0 2	1 0 2	1 0 1	1 0 1	1 0 0	9 8	
			7 . 0	1 0 7	1 0 6	1 0 6	1 0 5	1 0 6	1 0 6	1 0 5	1 0 4	1 0 4	1 0 4	1 0 3	1 0 3	1 0 2	1 0 2	1 0 1	1 0 1	9 9	
			1 0 . 0	1 0 8	1 0 7	1 0 7	1 0 6	1 0 6	1 0 6	1 0 6	1 0 5	1 0 4	1 0 4	1 0 4	1 0 3	1 0 2	1 0 2	1 0 2	1 0 2	9 9	

