

屋内照明器具特性	
品番 (品名)	S L D 1 0 2 3 L
光源	L E D 2 7 0 0 _ 7 0 _ 9 0 × 1 9 0 . 0 l m
管理番号	K 0 1 7 0 8 8 7 (0) D R 1
B Z 分類	B Z 1

器具効率		9 8 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																		Z C M	
下方光束		9 8 %																					
保守率		良 中 否	0 . 6 7	0 . 6	9 5	9 2	9 0	8 9	9 5	9 2	9 0	8 9	9 4	9 1	9 0	8 9	9 3	9 1	9 0	8 8	8 8		
			0 . 6 3	0 . 8	9 7	9 5	9 3	9 2	9 7	9 4	9 3	9 1	9 6	9 4	9 2	9 1	9 5	9 3	9 2	9 1	9 0		
			0 . 5 6	1 . 0	9 9	9 7	9 5	9 3	9 8	9 6	9 5	9 3	9 7	9 5	9 4	9 3	9 6	9 5	9 3	9 3	9 2		
				1 . 2 5	1 0 0	9 8	9 6	9 5	1 0 0	9 8	9 6	9 5	9 8	9 7	9 5	9 4	9 7	9 6	9 5	9 4	9 3		
下方投影面積		c m ²	1 . 5	1 0 1	9 9	9 8	9 6	1 0 0	9 9	9 7	9 6	9 9	9 8	9 6	9 5	9 8	9 7	9 6	9 5	9 4			
			等価発光面積		c m ²	2 . 0	1 0 2	1 0 1	9 9	9 8	1 0 1	1 0 0	9 9	9 8	1 0 0	9 9	9 8	9 7	9 9	9 8	9 7	9 6	9 4
取付 高さ	器具間隔最大限		2 . 5	1 0 3	1 0 2	1 0 0	9 9	1 0 2	1 0 1	1 0 0	9 9	1 0 0	9 9	9 9	9 8	9 9	9 8	9 7	9 7	9 5			
	横方向 (A)	縦方向 (B)	3 . 0	1 0 3	1 0 2	1 0 1	1 0 0	1 0 3	1 0 1	1 0 0	1 0 0	1 0 1	1 0 0	9 9	9 8	9 9	9 8	9 8	9 7	9 5			
H m	0 . 2 1 H m	0 . 2 1 H m	4 . 0	1 0 4	1 0 3	1 0 2	1 0 1	1 0 3	1 0 2	1 0 1	1 0 1	1 0 1	1 0 1	1 0 0	9 9	1 0 0	9 9	9 8	9 8	9 6			
			5 . 0	1 0 4	1 0 4	1 0 3	1 0 2	1 0 3	1 0 3	1 0 2	1 0 1	1 0 2	1 0 1	1 0 0	1 0 0	1 0 0	9 9	9 9	9 8	9 6			
			7 . 0	1 0 5	1 0 4	1 0 4	1 0 3	1 0 4	1 0 3	1 0 3	1 0 2	1 0 2	1 0 1	1 0 1	1 0 1	1 0 0	1 0 0	9 9	9 9	9 7			
			1 0 . 0	1 0 5	1 0 5	1 0 4	1 0 4	1 0 4	1 0 4	1 0 3	1 0 3	1 0 2	1 0 2	1 0 1	1 0 1	1 0 0	1 0 0	9 9	9 9	9 7			

