

屋内照明器具特性	
品番 (品名)	S L B 1 5 1 8 2 W
光源	LDA7L-D-G/S/Z6 ×2 810.0 lm
管理番号	K0172592 (0) DB 1
BZ分類	BZ5

器具効率		43 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束 下方光束		43 %	室指数	照明率 (X0.01) ZCM																	
保守率		良 中 否	0.63	0.6	24	19	16	13	24	19	16	13	23	18	15	13	22	18	15	13	12
			0.6	0.8	29	24	20	18	28	23	20	18	27	23	20	18	26	22	20	18	17
			0.56	1.0	31	27	24	21	31	26	23	21	29	26	23	21	28	25	23	21	20
				1.25	34	30	27	24	33	29	27	24	32	29	26	24	31	28	26	24	23
下方投影面積		cm ²	1.5	36	32	29	27	35	32	29	27	34	31	28	26	32	30	28	26	25	
等価発光面積		cm ²	2.0	38	35	32	30	37	35	32	30	36	34	32	30	35	33	31	30	28	
取付 高さ	器具間隔最大限		2.5	40	37	35	33	39	36	34	33	38	36	34	32	36	35	33	32	31	
	横方向 (A) 縦方向 (B)		3.0	41	38	36	35	40	38	36	34	39	37	35	34	38	36	35	33	32	
H m	1.26 H m	1.26 H m	4.0	42	40	38	37	41	40	38	37	40	39	37	36	39	38	37	36	35	
			5.0	43	41	40	39	42	41	39	38	41	40	39	38	40	39	38	37	36	
			7.0	44	43	41	41	43	42	41	40	42	41	40	39	41	40	39	39	38	
			10.0	44	44	43	42	44	43	42	42	43	42	41	41	42	41	41	40	39	

