

屋内照明器具特性	
品番 (品名)	S L B 1 5 1 3 2 W
光源	LDA7L - D - G / S / Z6 ×1 810.0 lm
管理番号	K0172591 (0) DB 1
B Z 分類	BZ5

器具効率		46 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z CM																
保守率		良 中 否	0.63	0.6	26	21	17	14	26	20	17	14	24	20	17	14	23	19	16	14	13
			0.6	0.8	31	26	22	19	30	25	22	19	29	25	21	19	28	24	21	19	18
			0.56	1.0	34	29	25	23	33	29	25	23	32	28	25	23	31	27	25	22	21
				1.25	37	32	29	26	36	32	29	26	34	31	28	26	33	30	28	26	25
下方投影面積 等価発光面積		cm ²	1.5	39	35	31	29	38	34	31	29	36	33	31	28	35	32	30	28	27	
			2.0	41	38	35	33	40	37	35	33	39	36	34	32	38	35	34	32	31	
			2.5	43	40	37	35	42	39	37	35	41	38	36	35	39	37	36	34	33	
取付 高さ	器具間隔最大限		3.0	44	41	39	37	43	41	39	37	42	40	38	37	41	39	37	36	35	
	横方向 (A)	縦方向 (B)	4.0	45	43	42	40	45	43	41	40	43	42	40	39	42	41	40	39	37	
H m	1.26 H m	1.26 H m	5.0	46	45	43	42	45	44	43	41	44	43	42	41	43	42	41	40	39	
			7.0	47	46	45	44	46	45	44	43	45	44	43	43	44	43	43	42	41	
			10.0	48	47	46	45	47	46	46	45	46	45	45	44	45	44	44	43	42	

