

屋内照明器具特性	
品番 (品名)	S L B 8 1 6 7 8
光源	LDA3 L - E17 / C / W ×1 280.0 l m
管理番号	K0157684 (0) DB 1
B Z 分類	BZ7 / 0.7 / BZ6 / 0.9 / BZ7

器具効率		87 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %
						室指数	照明率 (X0.01) Z CM															
保守率		良 中 否	0.63	0.6	42	31	24	19	39	29	23	18	33	26	20	16	29	22	18	15	11	
			0.6	0.8	49	39	32	26	46	36	30	25	39	32	26	22	34	28	23	20	15	
			0.56	1.0	54	44	37	32	51	41	35	30	43	36	31	27	37	31	27	23	18	
				1.25	59	50	42	37	55	47	40	35	47	41	35	31	40	35	31	27	21	
下方投影面積		cm ²		1.5	62	54	47	41	58	50	44	39	50	44	39	35	43	38	34	30	23	
等価発光面積			cm ²	2.0	67	60	53	48	63	56	50	45	54	49	44	40	46	42	39	35	27	
取付高さ	器具間隔最大限			2.5	70	64	58	53	66	60	54	50	57	52	48	44	49	45	42	39	30	
横方向 (A)		縦方向 (B)		3.0	73	66	61	57	68	62	58	54	59	55	51	48	51	47	44	42	32	
H m	1.37 H m	1.42 H m	4.0	76	70	66	62	71	66	62	59	62	58	55	52	53	51	48	46	36		
			5.0	77	73	69	66	73	69	65	62	64	61	58	55	55	53	50	48	38		
			7.0	80	76	73	70	75	72	69	66	66	63	61	59	57	55	54	52	41		
			10.0	82	79	77	74	77	75	72	70	68	66	64	62	59	58	56	55	44		

