

屋内照明器具特性	
品番 (品名)	X F X 4 2 0 K E L
光源	LED3000_85_2250 ×1 2250.0 l m
管理番号	K0192151 (0) D 1
B Z 分類	B Z 5 / 2 . 8 / B Z 4

器具効率		1 0 0 %		反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %			
					壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %							
					床	1 0 %					1 0 %					1 0 %					1 0 %					0 %			
上方光束		1 %		室指数	照明率 (X 0 . 0 1)																				Z C M				
下方光束		9 9 %																											
保守率		良 中 否	0 . 8 1	0 . 6	5 7	4 5	3 7	3 2	5 6	4 4	3 7	3 2	5 3	4 3	3 6	3 1	5 1	4 2	3 6	3 1	2 9								
			0 . 7 7	0 . 8	6 7	5 6	4 8	4 2	6 6	5 5	4 7	4 2	6 3	5 3	4 7	4 2	6 0	5 2	4 6	4 1	3 9								
			0 . 6 8	1 . 0	7 4	6 3	5 5	5 0	7 2	6 2	5 5	5 0	6 9	6 1	5 4	4 9	6 6	5 9	5 3	4 9	4 6								
				1 . 2 5	8 0	7 0	6 3	5 7	7 8	6 9	6 2	5 7	7 5	6 7	6 1	5 7	7 2	6 6	6 0	5 6	5 4								
下方投影面積		c m ²		1 . 5	8 4	7 5	6 8	6 3	8 2	7 4	6 8	6 3	7 9	7 2	6 7	6 2	7 6	7 0	6 5	6 1	5 9								
				2 . 0	9 0	8 2	7 6	7 2	8 8	8 1	7 6	7 1	8 5	7 9	7 4	7 0	8 2	7 7	7 3	6 9	6 7								
等価発光面積		c m ²		2 . 5	9 3	8 7	8 2	7 7	9 1	8 6	8 1	7 7	8 8	8 4	7 9	7 6	8 6	8 1	7 8	7 5	7 2								
				3 . 0	9 6	9 0	8 6	8 2	9 4	8 9	8 5	8 1	9 1	8 7	8 3	8 0	8 8	8 5	8 2	7 9	7 6								
1 . 5 m		1 . 9 4 m		2 . 1 1 m		4 . 0	9 9	9 5	9 1	8 7	9 7	9 3	9 0	8 7	9 4	9 1	8 8	8 5	9 2	8 9	8 6	8 4	8 1						
2		2 . 5 6		2 . 6 6		5 . 0	1 0 1	9 7	9 4	9 1	9 9	9 6	9 3	9 0	9 6	9 4	9 1	8 9	9 4	9 1	8 9	8 7	8 4						
2 . 5		3 . 1 8		3 . 2 2		7 . 0	1 0 3	1 0 0	9 8	9 6	1 0 1	9 9	9 7	9 5	9 9	9 7	9 5	9 3	9 6	9 4	9 3	9 1	8 8						
3		3 . 8		3 . 8 1		1 0 . 0	1 0 4	1 0 3	1 0 1	9 9	1 0 3	1 0 1	1 0 0	9 8	1 0 0	9 9	9 8	9 6	9 8	9 7	9 5	9 4	9 1						

