

屋内照明器具特性	
品番 (品名)	X F X 4 3 0 T E N
光源	LED5000_85_3110 ×1 3110.0 lm
管理番号	K0192145 (0) D 1
B Z 分類	B Z 5

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
上方光束		0 %		床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
下方光束		1 0 0 %	室指数	照明率 (X 0 . 0 1) Z C M																	
保守率		良 中 否	0 . 8 3	0 . 6	5 6	4 4	3 6	3 0	5 5	4 3	3 5	3 0	5 2	4 2	3 5	3 0	5 0	4 1	3 4	3 0	2 8
			0 . 8 1	0 . 8	6 6	5 4	4 6	4 0	6 4	5 3	4 6	4 0	6 1	5 2	4 5	4 0	5 9	5 0	4 4	3 9	3 7
			1 . 0	7 2	6 1	5 3	4 7	7 1	6 0	5 3	4 7	6 8	5 9	5 2	4 7	6 5	5 7	5 1	4 6	4 4	
			0 . 7 7	1 . 2 5	7 8	6 8	6 0	5 5	7 7	6 7	6 0	5 4	7 3	6 5	5 9	5 4	7 0	6 4	5 8	5 3	5 1
下方投影面積		cm ²	1 . 5	8 2	7 3	6 6	6 0	8 1	7 2	6 5	6 0	7 7	7 0	6 4	5 9	7 4	6 8	6 3	5 9	5 6	
等価発光面積		cm ²	2 . 0	8 8	8 0	7 4	6 8	8 6	7 9	7 3	6 8	8 3	7 7	7 2	6 7	8 0	7 5	7 0	6 6	6 4	
取付 高さ	器具間隔最大限		2 . 5	9 2	8 5	7 9	7 4	9 0	8 4	7 8	7 4	8 7	8 1	7 7	7 3	8 4	7 9	7 5	7 2	6 9	
	横方向 (A)	縦方向 (B)	3 . 0	9 4	8 8	8 3	7 8	9 2	8 7	8 2	7 8	8 9	8 5	8 0	7 7	8 6	8 2	7 9	7 6	7 3	
1 . 5m	1 . 9 6 m	2 . 1 m	4 . 0	9 7	9 2	8 8	8 4	9 6	9 1	8 7	8 4	9 3	8 9	8 5	8 2	9 0	8 7	8 4	8 1	7 8	
2	2 . 5 8	2 . 6 4	5 . 0	9 9	9 5	9 1	8 8	9 8	9 4	9 0	8 7	9 5	9 2	8 9	8 6	9 2	8 9	8 7	8 5	8 2	
2 . 5	3 . 2 1	3 . 2	7 . 0	1 0 2	9 8	9 6	9 3	1 0 0	9 7	9 5	9 2	9 7	9 5	9 3	9 0	9 5	9 3	9 1	8 9	8 6	
3	3 . 8 4	3 . 7 8	1 0 . 0	1 0 3	1 0 1	9 9	9 7	1 0 2	1 0 0	9 8	9 6	9 9	9 8	9 6	9 4	9 7	9 5	9 4	9 2	8 9	

