

屋内照明器具特性	
品番 (品名)	X F X 4 6 0 F E W
光源	LED4000_85_6180 ×1 6180.0 lm
管理番号	K0192928 (0) DB 1
B Z 分類	B Z 4

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束 下方光束		100 %	室指数	照明率 (X0.01) Z C M																	
保守率		良 中 否	0.81	0.6	60	48	41	36	59	48	41	36	56	47	40	36	54	46	40	36	34
			0.77	0.8	70	60	53	47	69	59	52	47	66	58	52	47	64	57	51	47	45
			0.68	1.0	77	67	60	55	76	67	60	55	73	65	59	55	70	64	58	54	52
				1.25	83	74	68	63	81	73	67	62	79	72	66	62	76	70	65	62	59
下方投影面積		c m ²		1.5	87	79	73	68	85	78	72	68	82	76	71	67	80	75	70	67	64
等価発光面積			c m ²	2.0	92	86	80	76	90	84	80	75	88	83	78	75	85	81	77	74	72
取付 高さ	器具間隔最大限		2.5	95	90	85	81	94	89	84	81	91	87	83	80	88	85	82	79	76	
	横方向 (A) 縦方向 (B)		3.0	97	93	88	85	96	91	88	84	93	89	86	83	91	87	85	82	80	
1.5m	2.02 m	2.13 m	4.0	100	96	93	90	99	95	92	89	96	93	90	88	93	91	89	87	84	
2	2.67	2.69	5.0	102	99	96	93	100	97	95	93	98	95	93	91	95	93	91	90	87	
2.5	3.32	3.26	7.0	104	101	99	97	102	100	98	96	100	98	96	95	97	96	94	93	90	
3	3.97	3.85	10.0	105	103	102	100	104	102	101	99	101	100	99	98	99	98	97	96	93	

