

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | X F X 4 4 2 F E N            |
| 光源       | LED5000_85_2580 ×1 2580.0 lm |
| 管理番号     | K0192932 ( 0 ) DB 1          |
| BZ分類     | BZ2/2.3/BZ1/3.5/BZ2/8.5/BZ1  |

| 器具効率   |  |        | 100 %           |      | 反射率  | 天井                | 80 % |     |     |     | 70 % |     |     |     | 50 % |     |     |    | 30 % |    |    |    | 0 % |
|--------|--|--------|-----------------|------|------|-------------------|------|-----|-----|-----|------|-----|-----|-----|------|-----|-----|----|------|----|----|----|-----|
|        |  |        |                 |      |      | 壁                 | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10 | 70   | 50 | 30 | 10 | 0 % |
|        |  |        |                 |      |      | 床                 | 10 % |     |     |     | 10 % |     |     |     | 10 % |     |     |    | 10 % |    |    |    | 0 % |
|        |  |        |                 |      |      | 照明率 ( X0.01 ) ZCM |      |     |     |     |      |     |     |     |      |     |     |    |      |    |    |    |     |
| 保守率    |  |        | 良<br>中<br>否     | 0.81 | 0.6  | 68                | 58   | 51  | 47  | 66  | 57   | 51  | 47  | 64  | 56   | 51  | 47  | 63 | 55   | 50 | 47 | 45 |     |
|        |  |        |                 | 0.77 | 0.8  | 78                | 70   | 64  | 60  | 77  | 69   | 64  | 60  | 75  | 68   | 63  | 60  | 73 | 67   | 63 | 59 | 58 |     |
|        |  |        |                 | 0.68 | 1.0  | 85                | 78   | 72  | 68  | 84  | 77   | 72  | 68  | 82  | 76   | 71  | 68  | 79 | 74   | 70 | 67 | 66 |     |
|        |  |        |                 |      | 1.25 | 90                | 84   | 79  | 75  | 89  | 83   | 78  | 75  | 86  | 81   | 77  | 74  | 84 | 80   | 77 | 74 | 72 |     |
| 下方投影面積 |  |        | cm <sup>2</sup> | 1.5  | 93   | 87                | 83   | 80  | 92  | 87  | 83   | 79  | 90  | 85  | 82   | 79  | 87  | 84 | 81   | 78 | 76 |    |     |
|        |  |        |                 | 2.0  | 97   | 93                | 89   | 86  | 96  | 92  | 88   | 85  | 94  | 90  | 87   | 85  | 91  | 88 | 86   | 84 | 82 |    |     |
| 等価発光面積 |  |        | cm <sup>2</sup> | 2.5  | 100  | 96                | 93   | 90  | 98  | 95  | 92   | 89  | 96  | 93  | 91   | 88  | 94  | 91 | 89   | 87 | 85 |    |     |
|        |  |        |                 | 3.0  | 101  | 98                | 95   | 93  | 100 | 97  | 94   | 92  | 98  | 95  | 93   | 91  | 95  | 93 | 91   | 90 | 88 |    |     |
| 1.5m   |  | 2.18 m | 2.05 m          | 4.0  | 103  | 100               | 98   | 96  | 102 | 99  | 97   | 96  | 99  | 98  | 96   | 94  | 97  | 96 | 94   | 93 | 91 |    |     |
| 2      |  | 2.9    | 2.58            | 5.0  | 104  | 102               | 100  | 99  | 103 | 101 | 99   | 98  | 101 | 99  | 98   | 96  | 98  | 97 | 96   | 95 | 92 |    |     |
| 2.5    |  | 3.62   | 3.14            | 7.0  | 105  | 104               | 102  | 101 | 104 | 103 | 102  | 100 | 102 | 101 | 100  | 99  | 100 | 99 | 98   | 97 | 94 |    |     |
| 3      |  | 4.33   | 3.71            | 10.0 | 106  | 105               | 104  | 103 | 105 | 104 | 103  | 102 | 103 | 102 | 101  | 101 | 100 | 99 | 99   | 99 | 96 |    |     |

