

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | XF X4 6 3 F E D              |
| 光源       | LED6500_85_4090 ×1 4090.0 lm |
| 管理番号     | K0192933 ( 0 ) DB 1          |
| B Z 分類   | BZ2                          |

| 器具効率     |           | 100 %           | 反射率    | 天井   | 80 %            |     |     |     | 70 % |     |     |     | 50 % |     |     |     | 30 % |    |    |    | 0 %  |
|----------|-----------|-----------------|--------|------|-----------------|-----|-----|-----|------|-----|-----|-----|------|-----|-----|-----|------|----|----|----|------|
|          |           |                 |        | 壁    | 70              | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50 | 30 | 10 | 0 %  |
|          |           |                 |        | 床    | 10 %            |     |     |     | 10 % |     |     |     | 10 % |     |     |     | 10 % |    |    |    | 0 %  |
|          |           |                 |        | 室指数  | 照明率 ( X0.01)    |     |     |     |      |     |     |     |      |     |     |     |      |    |    |    | Z CM |
| 保守率      |           | 良<br>中<br>否     | 0.81   | 0.6  | 67              | 58  | 51  | 47  | 66   | 57  | 51  | 47  | 64   | 56  | 51  | 47  | 62   | 55 | 50 | 46 | 45   |
|          |           |                 | 0.77   | 0.8  | 78              | 69  | 63  | 59  | 77   | 69  | 63  | 59  | 74   | 67  | 62  | 59  | 72   | 66 | 62 | 58 | 57   |
|          |           |                 | 0.68   | 1.0  | 84              | 77  | 71  | 67  | 83   | 76  | 71  | 67  | 81   | 75  | 70  | 66  | 79   | 73 | 69 | 66 | 64   |
|          |           |                 |        | 1.25 | 89              | 83  | 78  | 74  | 88   | 82  | 77  | 74  | 86   | 80  | 76  | 73  | 84   | 79 | 75 | 73 | 71   |
| 下方投影面積   |           | cm <sup>2</sup> |        | 1.5  | 92              | 87  | 82  | 78  | 91   | 86  | 81  | 78  | 89   | 84  | 80  | 77  | 87   | 83 | 80 | 77 | 75   |
|          |           |                 | 等価発光面積 |      | cm <sup>2</sup> | 2.0 | 97  | 92  | 88   | 85  | 95  | 91  | 87   | 84  | 93  | 89  | 86   | 84 | 91 | 88 | 85   |
| 取付<br>高さ | 器具間隔最大限   |                 | 2.5    | 99   | 95              | 92  | 89  | 98  | 94   | 91  | 88  | 95  | 92   | 90  | 87  | 93  | 91   | 88 | 86 | 84 |      |
|          | 横方向 ( A ) | 縦方向 ( B )       | 3.0    | 101  | 97              | 94  | 92  | 99  | 96   | 94  | 91  | 97  | 94   | 92  | 90  | 95  | 93   | 91 | 89 | 87 |      |
| 1.5m     | 1.96 m    | 1.98 m          | 4.0    | 103  | 100             | 98  | 96  | 101 | 99   | 97  | 95  | 99  | 97   | 95  | 94  | 97  | 95   | 94 | 92 | 90 |      |
| 2        | 2.61      | 2.49            | 5.0    | 104  | 102             | 100 | 98  | 103 | 101  | 99  | 97  | 100 | 99   | 97  | 96  | 98  | 97   | 95 | 94 | 92 |      |
| 2.5      | 3.25      | 3.02            | 7.0    | 105  | 104             | 102 | 101 | 104 | 103  | 101 | 100 | 102 | 100  | 99  | 98  | 99  | 98   | 98 | 97 | 94 |      |
| 3        | 3.89      | 3.55            | 10.0   | 106  | 105             | 104 | 103 | 105 | 104  | 103 | 102 | 103 | 102  | 101 | 100 | 100 | 100  | 99 | 98 | 96 |      |

