

屋内照明器具特性	
品番 (品名)	XF X454FEW
光源	LED4000_85_3120 ×1 3120.0 lm
管理番号	K0192930 (0) DB 1
BZ分類	BZ2

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
上方光束		0 %	100 %	室指数	照明率 (X0.01) ZCM																		
下方光束																							
保守率		良 中 否	0.81	0.6	69	59	53	49	67	58	53	49	66	58	52	48	64	57	52	48	47		
			0.77	0.8	78	70	64	60	77	69	64	60	75	68	63	59	73	67	62	59	57		
			0.68	1.0	84	77	71	67	83	76	71	67	81	75	70	67	79	73	69	66	64		
				1.25	89	82	77	74	88	82	77	73	86	80	76	73	83	79	75	72	71		
下方投影面積		cm ²	1.5	92	86	82	78	91	86	81	78	89	84	80	77	86	83	79	77	75			
			等価発光面積		cm ²	2.0	96	92	88	84	95	91	87	84	93	89	86	83	90	87	85	82	80
取付 高さ	器具間隔最大限		2.5	99	95	91	88	98	94	91	88	95	92	89	87	93	90	88	86	84			
	横方向 (A) 縦方向 (B)		3.0	100	97	94	91	99	96	93	91	97	94	92	90	95	92	90	89	86			
1.5m	1.8 m	1.89 m	4.0	103	100	97	95	101	99	97	95	99	97	95	93	97	95	93	92	89			
2	2.38	2.34	5.0	104	101	99	98	102	100	99	97	100	98	97	95	98	96	95	94	91			
2.5	2.97	2.81	7.0	105	103	102	101	104	102	101	100	102	100	99	98	99	98	97	96	94			
3	3.55	3.3	10.0	106	105	104	103	105	104	103	102	103	102	101	100	100	99	98	95	95			

